

Project Number: 6-CO082.00

Mount Cooee Landfill Development Plan and Resource Recovery Centre Geotechnical Interpretive Report

27 April 2023



Contact Details

Nima Taghipouran

WSP
197 Rattray Street
Dunedin 9016
+64 3 471 5500
021 0857 1841
Nima.Taghipouran@wsp.com

Document Details:

Date: 27/04/2023
Reference: 6-CO082.00
Status: Final

Prepared by

Caitlin Hall



Graduate Engineering Geologist

Nima Taghipouran



Principal Geotechnical Engineer

Reviewed by

Greg Saul



Technical Principal

Approved for release by

Chris Fox



Project Director



Document History and Status

Revision	Date	Author	Reviewed by	Approved by	Status
A	06/04/2023	Caitlin Hall / Nima Taghipouran	Greg Saul	Chris Fox	Draft for Client Comments
B	27/04/2023	Caitlin Hall / Nima Taghipouran	Greg Saul	Chris Fox	Final

Revision Details

Revision	Details
A	Draft for Client Comments
B	Final



Contents

1	Introduction	1
1.1	Objectives.....	1
1.2	Relevant Reports	1
2	Site Description	1
2.1	Site Features and Operations	2
3	Proposed Development.....	3
4	Site Geology	4
4.1	Published Geology	4
4.2	Regional Geology	4
4.3	Geomorphology	5
4.4	Preliminary Geological Mapping.....	6
4.5	Active Faults.....	12
4.6	Hydrogeology.....	13
5	Geotechnical Investigations.....	13
5.1	Historic Investigations	13
5.2	Recent Investigations	13
6	Ground Conditions.....	14
6.1	Interpreted Ground Profile	14
6.2	Groundwater	16
6.3	Soil and Rock Permeability.....	17
6.4	Laboratory Testing	18
6.5	Design Parameters.....	18
7	Seismicity	19
7.1	Site Subsoil Class	19
7.2	Seismic Design Criteria.....	19
7.3	Seismic Loads.....	20
7.4	Liquefaction and Cyclic Softening.....	20
8	Geotechnical Considerations	22
8.1	Global Stability.....	22
8.2	Long-Term Settlements.....	24
8.3	Foundation Design Inputs	25
8.4	Existing Cut-off Wall Performance	25
8.5	Suitability of site Soils for Reuse as a natural Soil Liner	26

8.6	Proposed Liner for Landfill Expansion.....	26
8.7	Liner Settlements.....	27
9	Earthworks Considerations	27
9.1	Overview	27
9.2	Cut and Fill Batters	27
9.3	Material Re-use	28
10	Conclusions	28
11	Recommendations for Next Stage	29
12	References.....	30

List of Figures

Figure 1:	Indicative location of the Site (Image courtesy of DCC's Web Map).....	1
Figure 2:	Typical bond construction and sheet pile detail (Courtesy of Royds Consulting Limited, 1995).....	2
Figure 3:	Schematic elevation of cut-off wall (image courtesy of Royds Consulting Limited (1995)) 3	
Figure 4:	Sketch of the clay barrier beyond the two ends of the cut off wall (image courtesy of Royds Consulting Limited (1995)).....	3
Figure 5:	Published geology of the site (image courtesy of 1:250k GNS Science Web Map).....	4
Figure 6:	Indicative alignment of the historic stream through the site (image courtesy of Royds Consulting Limited (1994))	5
Figure 7:	Excerpt from Leapfrog with Royds Consulting Limited (1994) contours overlain on December 2022 aerial image.....	6
Figure 8:	View of cut slope at Site 2.....	7
Figure 9:	Photograph showing various sections of the cut slope	8
Figure 10:	Quartz veining and rip-up clasts in sandstone beds of section 1.....	9
Figure 11:	A photograph showing the localised alluvial deposits to the north of the proposed landfill expansion	11
Figure 12:	Nearest active faults to the site (image courtesy of the GNS Science Active Faults Database).....	12
Figure 13:	Indicative boundary between 'eastern' and 'western' Sections.....	14
Figure 14:	Plot of groundwater levels recorded within standpipe piezometers since October 2022	17
Figure 15:	Published solid waste strength parameters (Singh and Murphy 1990) – (refer Qian et al 2002)	19

List of Tables

Table 1:	Summary ground profile for the eastern section of the site.....	15
Table 2:	Summary ground profile for the western section of the site	16
Table 3:	Summary preliminary design parameters.....	18
Table 4:	Suggested refuse parameters.....	19
Table 5:	Summary seismic loads for the site	20
Table 6:	Summary Atterberg Limits test results in BH1.....	21
Table 7:	Summary preliminary global stability assessment results	23
Table 8:	Summary of the stability assessment results for the existing landfill	23
Table 9:	Summary cut slope stability assessment results.....	24



List of Appendices

Appendix A – Site Plan

Appendix B – Preliminary Layout Plan

Appendix C – Machine Borehole Logs and Photographs

Appendix D - Geological Mapping Photographs and Geological Sections

Appendix E - Selected Liquefaction Assessment Outputs

Appendix F – Selected Slope/W Outputs

Disclaimers and Limitations

This report ('**Report**') has been prepared by WSP exclusively for Clutha District Council ('**Client**') in relation to the geotechnical interpretation and preliminary assessments of the existing Mount Cooee landfill and the proposed expansion. The scope of this report is to present the findings from the preliminary geotechnical assessments to inform the resource consent renewal for the existing landfill and preliminary design of the proposed landfill ('**Purpose**'). The findings in this Report are based on and are subject to the assumptions specified in the Report and the Offer of Service dated 31 August 2022 and the subsequent Confirmation Briefing Notice (CBN) dated 19 September 2022. WSP accepts no liability whatsoever for any reliance on or use of this Report, in whole or in part, for any use or purpose other than the Purpose or any use or reliance on the Report by any third party.

In preparing the Report, WSP has relied upon data, surveys, analyses, designs, plans and other information ('**Client Data**') provided by or on behalf of the Client. Except as otherwise stated in the Report, WSP has not verified the accuracy or completeness of the Client Data. To the extent that the statements, opinions, facts, information, conclusions and/or recommendations in this Report are based in whole or part on the Client Data, those conclusions are contingent upon the accuracy and completeness of the Client Data. WSP will not be liable in relation to incorrect conclusions or findings in the Report should any Client Data be incorrect or have been concealed, withheld, misrepresented or otherwise not fully disclosed to WSP.

1 Introduction

1.1 Objectives

WSP have been engaged by the Clutha District Council (CDC) to provide engineering services for the renewal and development of the Mt Cooee Landfill ('landfill') in Balclutha. The scope of services was presented in the WSP Offer of Service dated 6 August 2021.

As part of the project, WSP undertook deep ground Investigations in October and November 2022 to inform the variability of ground and groundwater conditions across the site. A summary of the factual data from the investigations was presented in the WSP report 'Mt Cooee Landfill Development Plan and Resource Recovery Centre – Geotechnical Factual Report – Rev 2' dated 31 March 2023 (WSP, March 2023).

This report provides a summary of a preliminary geotechnical assessment for the resource consent renewal for the existing landfill and the preliminary design of the proposed landfill expansion.

1.2 Relevant Reports

This report should be read in conjunction with the following reports:

- 'A Report of Site Investigations at the Mount Cooee Landfill', by Royds Consulting Limited, May 1994 (Royds Consulting Limited, 1994).
- 'Mt Cooee Landfill Development Plan and Resource Recovery Centre – Geotechnical Factual Report' by WSP dated 31 March 2023, Revision 2 (WSP, March 2023).
- 'Mt Cooee Landfill Development Plan – Sheet Pile Cut-off Review Report (Final Issue)' by WSP dated 5 April 2023 (WSP, April 2023).

2 Site Description

The Mt Cooee Landfill site (the 'site') is situated on the Kaitangata Highway in the outskirts of Balclutha. The site encompasses 2 lots on the property DP 12203 and has a total area of approximately 12.8 hectares. The approximate location of the site relative to Balclutha is shown on Figure 1 below.




Figure 1: Indicative location of the Site (Image courtesy of DCC's Web Map)

The site is situated in a gently sloping valley that drops southwest towards the Clutha River/ Mata-Au. The site is bounded by the Dunedin – Invercargill Railway Line (the ‘Railway Line’) to the north and the Kaitangata Highway to the south. The Highway runs adjacent to the Clutha River / Mata-Au. The site adjoins private farmland to the east, from which it is screened by a windbreak of large macrocarpa trees. Access to the site is via a driveway off the Kaitangata Highway.

The area to the east of the site is rural land, with the nearest dwelling roughly 250 m from the site boundary. The Balclutha Golf Course is situated across the Railway Line to the north of the site.

2.1 Site Features and Operations

The landfill has been operating since about 1985 and is currently operated under the classification of a “Class 1” landfill in accordance with WasteMINZ Technical Guidelines to Land 2022 (WasteMINZ, 2022). The landfill is currently the only municipal solid waste landfill in the Clutha District, servicing a district population of around 18,400, including approximately 4,000 in the immediate township of Balclutha. The landfill receives approximately 9,000 tonnes of waste per year, including waste received through Council’s kerbside refuse collection service (servicing around 6,000 households) and ten public drop-off facilities/transfer stations, along with residential, commercial, and industrial customers.

Site operations are managed by a private contractor, with general waste deposited directly to the tip face and green waste and hardfill deposited on an area of capped landfill. Resource Recovery facilities are situated across the southern end of the landfill on hard stand areas.

The existing landfill is not lined but a low permeability cut off element was designed under the southern perimeter bund comprising a clay filled trench and an approximately 46m long section of sheet pile to bedrock. The indicative extents of the perimeter bund and the sheet pile wall are shown on the Site Plan – Appendix A. Based on the review of available information by Royds Consulting Limited (1995), the wall was constructed circa 1995 using a total of 115 sheet pile sections, each nominally 0.4m wide. The records indicate the wall was driven to refusal on top of weathered greywacke bedrock, with pile lengths ranging between 6 to 11 m along the wall. A typical cross section of the bund and the cut off wall is presented on Figure 2 below. Further details of the cut off wall are presented in WSP (April 2023).




Figure 2: Typical bund construction and sheet pile detail (Courtesy of Royds Consulting Limited, 1995)

A historic drawing by Royds Consulting Limited (1995) suggests the sheet pile wall is situated along the central section of the clay bund, where the bedrock is deepest at the valley floor (in the order of 10m or so). Instead of the sheet pile wall, it appears that an approximately 1.0m wide low permeability clay barrier was constructed along the clay bund beyond the two ends of the sheet

pile wall, where bedrock becomes progressively shallower. An extract from the drawing is presented as Figures 3 and 4 below.




Figure 3: Schematic elevation of cut-off wall (image courtesy of Royds Consulting Limited (1995))




Figure 4: Sketch of the clay barrier beyond the two ends of the cut off wall (image courtesy of Royds Consulting Limited (1995))

3 Proposed Development

The existing landfill is now nearing the closure design level and therefore requires upgrading and reconsenting to continue operation as the main landfill in Balclutha. The proposed development to enhance the capacity of the existing landfill mainly includes the following:

- Improved public waste receipt facilities including the development of a Resource Recovery Centre (RCC) and associated carparking space to the east of the existing access road and a Transfer Station and associated facilities towards the centre of the site (to the east of the existing weighbridge).
- Landfill expansion to the east and south of the existing landfill operation.
- A new road providing access to the site.

The new landfill will be fully lined and consistent with the WasteMINZ Technical Guidelines for Disposal to Land (WasteMINZ, October 2022). The landfill is proposed to be constructed in 4 stages, with a clockwise staging sequence commencing with the cell at the north alongside the Railway Line.

A Preliminary Layout Plan showing the main features of the proposed development is presented in Appendix B. Further details of the proposed development are presented in the WSP Design Report titled 'Mount Cooee Landfill Expansion' dated 6 April 2023.

4 Site Geology

4.1 Published Geology

The Published Geology Web Map by GNS Science indicates that the site is underlain by two geological units: the Caples Terrane (Unit YTr) across the northern half of the site and the Pakihi Supergroup (Unit Q1a) across the southern half. An extract from the Web Map showing the indicative boundary between the two geological units is shown on

Figure 5 below.

The Caples Group is described as massive to well bedded grey, red and green sandstone with sub-ordinate mudstone and granular conglomerate. The Pakihi Supergroup consists of unconsolidated gravel, sand, and peats in modern stream beds as well as flood plains with minor riverbank swamps.




Figure 5: Published geology of the site (image courtesy of 1:250k GNS Science Web Map)

4.2 Regional Geology

The Balclutha region is situated in a region of complex arrangement of tectonic terranes. These tectonic terranes form the basement of New Zealand, originating from the sedimentary rocks of the accretionary wedge of Gondwana (Mortimer, 2004). The Clutha region, and specifically Balclutha, lies within a zone of regional metamorphism, where rocks are buried due to tectonic processes, heated and then brought back to the surface through faulting and folding over millennia.

The overall geology of the region typically consists of highly fractured and tectonically disturbed basement rocks overlain by alluvial deposits associated with the Clutha River / Mata-Au.

4.3 Geomorphology

The site occupies an ancient floodplain, overlain by alluvial gravels. The general topography of the site has been extensively modified by earthworks for the current landfill at the northern extent of the site, and preparation of the proposed landfill at the eastern section of the site. The south-eastern section of the site, where BH3 – BH6 are situated is a gently sloping grazing paddock for farmstock and has remained relatively unchanged since the establishment of the current landfill.

The presence of a paleo-valley inferred from reviewing available topographical maps was noted trending northeast to southwest through the site. A review of the report by Royds Consulting Limited (1994) and historic imagery confirmed the presence of an incised stream bed feature oriented in the northeast to southwest direction and inferred to be running under the current landfill site. Royds Consulting Limited (1994) identified this area as a swamp that was heavily vegetated at the time of their report. The indicative alignment of the historic stream is shown on Figure 6 below and overlain on survey imagery on Figure 7 on the next page.




Figure 6: Indicative alignment of the historic stream through the site (image courtesy of Royds Consulting Limited (1994))




Figure 7: Excerpt from Leapfrog with Royds Consulting Limited (1994) contours overlain on December 2022 aerial image

4.4 Preliminary Geological Mapping

Preliminary geological mapping of the available exposures across the site were carried out by WSP Engineering Geologists in 2021 and 2023 to inform the assessments. The mapping was carried out across most of the site where access to outcrops was possible, with greater focus on the proposed landfill expansion area to the east of the site as well the area to the south of the existing landfill, where new landfill facilities are generally concentrated.

The mapping features were limited to exposed rock cuttings from the current earthworks operations on site. Measurements were obtained using a geologic compass to record the orientation of any bedding and jointing features within sites of interest.

Based on our field mapping observations, the alluvium is constrained to thin, isolated locations across the eastern section of the site, overlain by a thin layer of topsoil. The alluvium appears to be thicker and more consistent across the western section, with thickness of up to 6m encountered in BH1 at the south-western section of the site (south of the existing landfill).

The Caples Terrane bedrock underlying topsoil and alluvium across the entire site consists of interbedded sandstone and siltstone, which exhibits mm-scale sub-horizontal bedding features with localised shear zones ranging between a few mm's to ~0.5 m. The main findings from the preliminary mapping are presented below.

4.4.1 2021 Preliminary Mapping Findings

The preliminary mapping carried out in 2021 was constrained to three localised areas across the entire site, where rock exposures were observed. The indicative locations of the

mapping sites (referred to as sites 1 (2021) to site 3 (2021) hereafter) are shown in Appendix D.

A summary of the findings from the sites are presented below.

- The rock exposures consisted of interbedded sandstone and siltstone of Caples Terrane.
- The bedrock was found to be highly jointed, with defect spacings ranging between approximately 30 – 100 mm. The bedrock exhibited very close defect spacing (in the order of a few mm's).
- Slightly weathered to fresh rock was observed at sites 1 and 3. Site 3 consisted of a thin (<0.3m) layer of residual soils overlying bedrock, whilst rock was observed at surface at site 2 (refer
- Figure 8 below).



Figure 8: View of cut slope at Site 2

4.4.2 2023 Preliminary Mapping Findings

The preliminary mapping carried out in 2023 was mainly concentrated on the areas of proposed landfill expansion.

Mapping was also carried out in the southern section of the site where new facilities are proposed, and in particular the existing cut slope immediately to the south of the proposed building platforms. Excavation into this cut slope is currently proposed to form the building platforms and therefore a detailed inspection of this feature was carried out.

The main findings for the mapped areas are presented below and in Appendix D.

4.4.3 Existing Cut slope

Based on the visual inspection, the cut slope has been divided to three distinct sections (referred to as Sections 1 to 3 hereafter). A photograph showing the cut slope is presented on Figure 9 below, with further commentary in Appendix D.



Figure 9: Photograph showing various sections of the cut slope

A brief summary of the observations for each section is presented below.

Section 1

- This western section of the slope is typically 2m high, with its height increasing eastward towards Section 2. The slope is at typical angle of 1(V): 2(H).
- Based on discussions with the excavator operators on site, we understand this section of the cut slope is extremely difficult to excavate and many of their machines struggled to remove the top layer.
- The slope consists of interbedded sandstone and siltstone, light grey to dark grey where fresh. Some minor horizontal bedding was observed, though no obvious trend was established. Rip-up clasts were observed within localised areas of this section, typically associated with quartz veining and jointing (refer Figure 10). Rip-up clasts are typically clasts of muddy sediments of variable sizes found within sandstone.
- The slope face exhibits various jointing and fracturing throughout, with some veining in the order of a few mm's thick but in groups of up to ~0.5 m in thickness in localised areas (refer
- Figure 10).



Figure 10: Quartz veining and rip-up clasts in sandstone beds of section 1

No distinct boundary between Sections 1 and 2 was observed, with the change being gradational.

Section 2

- The middle section of the slope is the highest section, with the maximum height of up to 10m based on the site survey. The current slope is typically at a 1(V):1.5 (H) angle.
- At the time of the site visit, this section exhibited marginal surficial stability, with evidence of surficial rock dislodgement along the joints.
- Horizontal jointing of oxidised, highly fractured interbedded sandstone and siltstone was apparent along this section. Measurements were limited on this section due to the marginal stability at the time of the site visit. General observations concluded orientation of bedding to be slightly dipping to the southwest.

Section 3

- The eastern section is in the order of 1m to 2m high, at a typical angle of 1(V):1.5(H). This slope consists of bulbous, well rounded, and completely weathered sandstone and siltstone. The rock observed is generally light brown to light grey in colour and very friable. The quality of the rock mass is better (stronger/higher) in this area compared to sections 1 and 2.
- No distinct boundary between Sections 2 and 3 was apparent, although a gradational change from the completely weathered to highly weathered rock was observed.

4.4.4 Landfill Expansion Area

The proposed landfill expansion site has been excavated in some areas to expose fresh to slightly weathered interbedded rock (refer Appendix D for photographs). An approximately 1 m – 2 m thick layer of well-rounded alluvial deposits was observed at the north-eastern end of the site. These deposits were localised to only this section and are not considered to be continuous across the eastern section of the site.

Depositional bedding features were observed in the alluvium and flow direction was able to be determined by visually analysing the orientation of the quartz gravel in this layer. This paleo-flow direction suggests a south to southwestern trending flow. A photograph showing this section of the landfill is presented on

Figure 11 on the next page.

The remainder of the landfill expansion area was typically exposed to slightly weathered to moderately weathered interbedded sandstone and siltstone. No obvious bedding features were observed, and the outcrops were limited to machine excavated faces, which made geological interpretation difficult. Knowledge gathered from other locations across the site helped to confirm the general trend of bedding oriented south to southwest.




Figure 11: A photograph showing the localised alluvial deposits to the north of the proposed landfill expansion

4.4.5 Preliminary 3-Dimensional (3D) Geological Model

A preliminary 3D geological model of the entire site has been developed using the Leapfrog software by Seequent. The model is based on the historic and recent deep investigation data and utilises the preliminary mapping findings to extrapolate the ground conditions between the investigation points.

The current model has the following limitations:

- No investigations have been carried out within the existing landfill footprint at the north-western section of the site and therefore the ground conditions across this section are inferred based on the nearby boreholes, namely BH1, BH2, BH1 (Royds) and BH2 (Royds). It is anticipated that the alluvial deposits within the landfill footprint have been removed to date to create the landfill floor.
- No intrusive investigations were completed in the area to the east of the existing access road and the locations of the proposed RRC and Transfer Station. However, preliminary geological mapping has been utilised to inform the likely ground conditions.

The current model is considered adequate to inform the preliminary assessments.

4.4.6 Likely Slope Instability Mechanisms

Based on the site observations and preliminary mapping, the likelihood of deep-seated instability in the rock slopes across the site is considered to be low. The likely modes of failure are constrained to the surficial rock as blocky or wedge failure, expected along joint or sheared planes. Section 2 of the existing cut slope predominantly displayed this failure mechanism.

4.5 Active Faults

There are currently no active faults at the immediate site. However, the GNS Science Active Faults Database in 3 fault traces within the 100 km radius of the site. The faults and their characteristics are listed below.

- The Clifton Fault (#8677): This fault has a normal fault sense and a recurrence interval of IV (>5,000 to <= 10,000 years) and is approximately 11 km west of the landfill site.
- The Unknown Fault (#8994): There is currently no available information on the fault sense or recurrence interval of this fault, apart from the approximate location of the fault surface. This active fault is located within 5 km to the northeast of the site.
- The Titri Fault (#9954): This fault lies approximately 14 km to the northeast of the site and runs in the north-east/south-west direction. No recent rupture of this fault has been recorded, and it is estimated the last rupture has occurred in the late Quaternary (i.e. 0.5 – 1.0 million years ago) and GNS estimate a recurrence interval of 70,000 to 80,000 years.

The approximate locations of the faults relative to the site are shown on Figure 12 below.




Figure 12: Nearest active faults to the site (image courtesy of the GNS Science Active Faults Database)

Given the distances from the active faults to the site and their associated recurrence intervals, the risk of fault rupture affecting the site is anticipated to be low.

4.6 Hydrogeology

The current understanding of the groundwater system at the Mt Cooee Landfill site is that of a groundwater system dominated by flow through the Caples Terrane bedrock of various permeabilities. Some flow is also likely to occur through the overlying alluvial deposits, particularly in the valley floor that runs through the southwest side of the site where the alluvial sediments are generally thicker.

Groundwater level measurements in the historic and recent wells to date have not shown clear differences in groundwater levels within the bedrock and overlying alluvium. Therefore, the groundwater system is conceptualised as effectively one connected system. Groundwater is largely recharged by rainfall in the catchment and flows from the topographic highs at the north towards the southwest. Groundwater level measurements at the landfill and riverbank elevations (obtained from LiDAR) indicate that groundwater is likely connected to the Clutha River / Mata-Au and the river gains groundwater from the site.

5 Geotechnical Investigations

A summary of the historic and recent investigations carried out across the site is presented below.

5.1 Historic Investigations

Royd Consulting Limited (1994) carried out limited geotechnical investigations across the site in 1994. The purpose of the investigations was to obtain a better understanding of ground and groundwater conditions across the site to inform the developments at the time. The investigations included the following:

- A total of two boreholes (labelled BH1 (Royds) and BH2 (Royds) hereafter) to target depths of 15m and 9.5m bgl. The boreholes were drilled using the rotary air flush techniques between 28 January and 7 February 1994.
- 5 machine-excavated test pits, (labelled as trial pits No. 1 to No. 5) carried out on 11 February 1994.
- A total of 7 groundwater wells (GW1 – GW7) across the site to inform groundwater levels. Please note that only limited logs are available for the groundwater wells.

Indicative locations of the above investigation points are shown on the Site Plan – refer Appendix A. Further details of the investigations are presented in Royds Consulting Limited (1994).

5.2 Recent Investigations

Site-specific ground investigations were undertaken by WSP across the site between October and November 2022. The investigation points were spread across the entire site to assess the nature and variability of the ground conditions and allow groundwater and gas monitoring through the installation of the piezometers.

The investigations included the following:

- A total of ten machine boreholes (BH1 to BH10) to target depths ranging between 3.0 m and 11.6 m bgl for geotechnical and hydrogeological purposes. Drilling was undertaken using the rotary coring method in both soils and in rock. Boreholes were terminated upon proving a sufficient thickness of bedrock or reaching the pre-determined target depths.
- Installation of standpipe piezometers in BH1 to BH6 to allow groundwater monitoring purposes.
- Installation of a standpipe piezometer in BH10 for ground gas monitoring.

- Laboratory testing on selected samples of soils and rock (refer Section 6.4 for details).

The approximate locations of the machine boreholes are presented on the Site Plan – Appendix A. The borehole logs and photographs are presented in Appendix C. Further details of the investigations are presented in WSP (March 2023).

6 Ground Conditions

6.1 Interpreted Ground Profile

The soils and rock encountered within the historic and recent geotechnical investigation points are generally consistent with the published geology and comprise Caples Terrane bedrock across the site, overlain by topsoil and alluvial deposits.

For preliminary assessments, we have divided the ground profile across the entire site to two distinct profiles, referred to as 'eastern' and 'western' sections hereafter. This is mainly due to the increased presence and thickness of alluvial deposits across the western section. The indicative boundary between the two sections is presented on Figure 13 below. The two profiles are further discussed below.



Figure 13: Indicative boundary between 'eastern' and 'western' Sections

6.1.1 Eastern Section Ground Profile

Based on the site investigation and preliminary geological mapping findings, the eastern section of the site is predominantly underlain by a typically less than 0.5m thick layers of topsoil (**Unit 1**) overlying Caples Terrane bedrock (**Unit 3**).

The machine boreholes BH6 – BH10 drilled near the location of the proposed landfill expansion indicate that the upper layer of the Caples Terrane bedrock generally consists of several sequences of 'highly to moderately weathered, weak to moderately strong

SANDSTONE/SILTSTONE' (**Unit 3b**), with a typical uncorrected SPT N value exceeding 50. This layer transitions to 'moderately to slightly weathered, moderately strong SANDSTONE/SILTSTONE' (**Unit 3c**) at depths typically ranging between 3m to 5m bgl. A typically 1.0m thick layer of 'completely weathered SANDSTONE/SILTSTONE' (Unit 3a) was encountered in some of the boreholes.

The bedrock was found to be highly fractured, with joints at very close spacing and a typical Rock Quality Designation (RQD) value of 0% in particular in weathered rock. Some variations in the strength and weathering of the rock were observed in the cores obtained from the boreholes. A thin layer (typically < 1m thick) of 'completely weathered, extremely weak SANDSTONE/SILTSTONE' (**Unit 3a**) was observed in some of the boreholes across the eastern section. This layer was generally recovered as 'stiff sandy/clayey SILT with low to moderate plasticity'.

As described under Section 4.3.4, an approximately 1m – 2 m thick layer of well-rounded alluvial deposits was observed to the north-east of the site. Layers of alluvial deposits less than 1m in thickness were also encountered in BH5 and BH3 to the south-east of the site. Based on site observations, we anticipate the alluvial deposits to be present localised pockets only and not be laterally continuous across the eastern section of the site.

A representative ground profile for the eastern section of the site is presented in Table 1 below. Please note that variations in the ground conditions, in particular the thickness of weathered rock may be anticipated.

A geological section (Section B – B') showing the variations in the ground conditions across the entire site is presented in Appendix D.

Table 1: Summary ground profile for the eastern section of the site

Unit ID	Unit Name	Generalised Unit Description	Typical Depth Range (m RL) ¹	SPT N Value Range ²
1	Topsoil	Topsoil.	11.0 – 10.5	Not tested
3	3(a)	Completely weathered, extremely weak SANDSTONE / SILTSTONE	10.5 – 9.5	56 - 60+ (typ. 60+)
	3(b)	Highly to moderately weathered, very weak to weak SANDSTONE / SILTSTONE	9.5 – 4.5	60+
	3(c)	Slightly weathered to fresh, moderately strong to strong SANDSTONE / SILTSTONE	< 4.5	60+

¹The depth ranges (in m RL) are generally based on considering 11m RL (based on NZVD 2016 datum) as the existing ground level at BH3 location, considering BH10 at the eastern end of the site as the datum. Due to variations in site topography, the depth ranges vary across the site.

²The SPT N values are uncorrected and based on blows per 300mm. Typical values are presented in brackets.

6.1.2 Western Section Profile

The intrusive investigation results and preliminary mapping findings indicate the ground conditions across the western section of the site are generally similar to the eastern section,

with the exception of a layer of 'Alluvium' encountered in the recent and historic machine boreholes.

Based on the investigation results, the western section of the site is underlain by an approximately a thin layer (typically < 1m) of topsoil (**Unit 1**), overlying alluvium (**Unit 2**). The alluvium is approximately 5.5m thick in BH1 and 2.5m thick in BH2 to the south and north of the existing landfill, respectively. The nature of alluvium appears to be highly variable, with BH1 indicating the layer to consist of thin layers of cohesive 'soft to firm silty CLAY with high plasticity' interbedded with 'sandy SILT/silty SAND with low plasticity'. In addition to the recent boreholes, alluvial deposits are inferred to be present in the historic BH2 (Royds) and appears to be continuous with variable thicknesses across the western section of the site.

Unit 2 is underlain by Caples Terrane bedrock (**Unit 3**), consisting of sequences of moderately to slightly weathered, highly fractured, fine fabric SANDSTONE and SILTSTONE. An approximately 1m thick layer of 'completely weathered, extremely weak SANDSTONE' was encountered in BH2. This layer was recovered as stiff to very stiff SILT.

A simplified ground profile for the western section of the site based on BH1 and BH2 is presented in Table 2 below. A geological section (Section A – A') showing the variations in the ground conditions across the western section of the site is presented in Appendix D.

Table 2: Summary ground profile for the western section of the site

Unit ID	Unit Name	Generalised Unit Description	Typical Depth Range (m RL) ¹	SPT N Value Range ²
1	Topsoil	Topsoil with trace rootlets and trace fine quartz gravel.	9.0 – 8.5	Not tested
2	Alluvium	Soft to firm silty CLAY, moist, high plasticity interbedded with loose silty fine to coarse SAND, low to no plasticity.	8.5 – 3.0	1 – 7 (typ. 5)
3	3(a)	Completely weathered, extremely weak SANDSTONE / SILTSTONE	3.0 – 2.0	56 - 60+ (typ. 60+)
	3(b)	Highly to moderately weathered, very weak to weak SANDSTONE / SILTSTONE	2.0 – 0.0	60+
	3(c)	Slightly weathered to fresh, moderately strong to strong SANDSTONE / SILTSTONE	< 0.0	60+

¹ The depth ranges (in m RL) are generally based on considering 9m RL (based on NZVD 2016 datum) as the ground level, considering BH1 at south-western end of the site as the datum. Due to variations in site topography, the depth ranges vary across the site.

² The SPT N values are uncorrected and based on blows per 300mm. Typical values are presented in brackets.

6.2 Groundwater

Groundwater was recorded at depths ranging between approximately 1.2 m and 5.6 m bgl within the machine boreholes during the investigation.

Several rounds of monitoring of the piezometers installed in BH1 – BH6 and BH10 have been completed on typically monthly basis since the drilling. A summary of the readings to date is presented in the WSP (March 2023). A plot of groundwater levels (in m RL based on the NZ Vertical Datum 2016) carried out to date is presented as Figure 14 below. The existing ground levels (in m RL) at borehole locations are presented on the plot legend.




Figure 14: Plot of groundwater levels recorded within standpipe piezometers since October 2022

As indicated on Figure 14 above, the long-term groundwater level is anticipated at depths ranging between 6m to 20m RL (in the order of 1m to 4m below existing ground levels) across the site, with flow towards the Clutha River / Mata-Au in the south. Across the western section of the site, long-term groundwater is anticipated to lie approximately 2m bgl and within the alluvial deposits. The piezometer readings in the boreholes across the eastern section suggest groundwater typically lies within the fractured rock or close to the interface between rock and overlying soils. Except for a groundwater level of 2.3m bgl (~ 18.7m RL) measured in October 2022, the piezometer readings in BH6 at the proposed landfill site have indicated dry conditions.

Elevated groundwater levels may be anticipated during heavy rainfalls and have been considered in the preliminary geotechnical analyses.

6.3 Soil and Rock Permeability

Permeability testing (include reference) of geological units on site to date indicate the hydraulic conductivities are in the order of 10^{-7} m/s in slightly weathered to fresh rock (**Unit 3(c)**). The hydraulic conductivities within weathered rock (**Unit 3(b)**) are found to have a wide range of 10^{-9} to 10^{-4} m/s. The wide range observed is likely due to the presence of fractures in the sandstone/siltstone.

The overlying alluvium is shown to have a hydraulic conductivity of 10^{-6} m/s. This is based on limited information from one well only (BH1) and is likely to vary given the interbedded and variable nature of this layer.

6.4 Laboratory Testing

Laboratory testing was undertaken by the WSP Laboratory (based in Christchurch) on selected soil samples recovered from BH1, BH8, and BH10. Testing includes the following:

- Atterberg Limits in accordance with NZS 4402: 1986: Test 2.1 - Test 2.5.
- Particle Size Distribution (PSD) in accordance with NZS 4402:1986: Test 2.8.4 (Washed Grading & Hydrometer Method)
- Uniaxial Compressive Strength (UCS) testing of intact rock core samples in accordance with ASTM D7012 – Test C (previously ASTM D2938).

A summary of the laboratory testing details and results is presented in WSP (March 2023).

Please note that due to the highly fractured nature of rock underlying the site, only limited suitable samples were available for laboratory testing.

6.5 Design Parameters

6.5.1 In-situ Soil and Rock Parameters

A set of preliminary design parameters has been derived for the in-situ soils and rock based on the ground investigation, limited laboratory testing results and our experience with local soils and rock.

The parameters are presented in Table 3 below, with typical parameters presented inside the brackets.

Table 3: Summary preliminary design parameters

Unit ID	Unit Name	Unit Weight γ , (kN/m ³)	Effective Cohesion c' , (kPa)	Friction Angle Φ , (Deg)	Undrained Shear Strength, S_u (kPa)
1	Topsoil	16 - 17 (16)	0 - 1 (1)	24 - 26 (25)	N/A
2	Alluvium	17 - 18 (17)	1 - 2 (1)	26 - 30 (28)	30 - 50 (30)
3a	Completely weathered, extremely weak SANDSTONE / SILTSTONE	19 - 20 (19)	3 - 6 (5)	26 - 30 (28)	100 - 200 (150)
3b	Highly to moderately weathered, very weak to weak SANDSTONE / SILTSTONE	20 - 22 (21)	15 - 25 (20)	38 - 42 (40)	300 - 500 (400)
3c	Slightly weathered to fresh, moderately strong to strong SANDSTONE / SILTSTONE	22 - 24 (23)	20 - 40 (30)	40 - 45 (44)	500 - 1000 (750)

6.5.2 Refuse Parameters

The nature and strength of refuse material is highly variable and difficult to measure. Research carried out by Singh and Murphy (1990) suggests that municipal waste can exhibit significant apparent cohesion or friction angles. A plot of the likely parameters for solid waste based on a combination of laboratory testing, in-situ testing and back calculations is presented as Figure 15.




Figure 15: Published solid waste strength parameters (Singh and Murphy 1990) – (refer Qian et al 2002)

A suggested range of parameters for the refuse is presented in Table 4 below, with typical values inside brackets. The preliminary stability assessments for the landfill expansion have considered relatively conservative, lower bound refuse parameters to assess the sensitivity of results to the input parameters. The parameters are based on the consideration the refuse is placed in thin layers and compacted.

Table 4: Suggested refuse parameters

Material Type	Unit Weight γ , (kN/m ³)	Effective Cohesion c' , (kPa)	Friction Angle Φ , (Deg)
Municipal Solid Waste	12 - 14 (13)	3 - 8 (5)	22 - 28 (25)

7 Seismicity

7.1 Site Subsoil Class

Bedrock was encountered at shallow depths (typically < 1m bgl) in the machine boreholes across the eastern section of the site. On this basis, the site subsoil class is considered to be 'B – Rock' for this section of the site (in accordance with NZS1170.5).

Alluvial deposits with thickness of up to 6m (based on BH1) were encountered across the western section of the site. We recommend site subsoil class 'C – Shallow Soils' be adopted for this section of the site.

7.2 Seismic Design Criteria

New Zealand has no specific standard developed to assess design earthquakes for landfills, and landfills are not specifically mentioned within NZS1170.0:2002. We have assessed the importance level of the landfill facility based on the following assumptions as described within Table 3.1 of NZS 1170.0: 2002:

- Low consequence for loss of human life.
- Considerable economic and environmental consequence.

Based on Tables 3.1 and 3.2 in NZS1170.0:2002, we consider the landfill to be an Importance Level 2 structure (i.e. *Normal structures and structures not in other importance levels*).

The landfill will have an operative life of approximately 35 years, followed by anticipated 15 - 20 years of aftercare. Therefore, we have adopted a design working life of 50 years in order to derive the seismic loads for the landfill.

7.3 Seismic Loads

Peak ground accelerations (PGAs) have been derived for liquefaction and global stability assessments in accordance with Section 6.2 of the current Waka Kotahi Bridge Manual using Equation 1 below:

$$C_o g \text{ (or PGA)} = C_{0,1000} \frac{R_u}{1.3} f g \quad \text{(Equation 1)}$$

PGAs have been derived based on the following parameters and presented in Table 5 below.

- Importance Level 2 (IL2) structure with a 50-year design life.
- Site subsoil classes 'B - Rock' for the eastern section and 'C - Shallow Soils' for the western section of the site (in accordance with NZS1170.5).
- f, site subsoil class factor = 1.33 for site subsoil class 'C' and 1.0 for site subsoil class 'B'.
- C_{0,1000}, 1000-year return period PGA coefficient = 0.22 (Balclutha).

Table 5: Summary seismic loads for the site

Seismic Case	Annual Probability of Exceedance ¹	Return Period Factor (R) ²	PGA (g)		Effective Magnitude
			Eastern Section	Western Section	
Serviceability Limit State (SLS)	1/25	0.25	0.04	0.06	6.0
Damage Control Limit State (DCLS)	1/500	1.0	0.17	0.23	

¹ Annual probabilities of exceedance (APE) are based on Table 3.3 NZS 1170.0, Table 3.5 NZS 1170.5 and Table 5.3 of the Bridge Manual.

² Return period factors are based on Table 3.5 of NZS1170.5 and Table 5.1 of the Bridge Manual

Please note the seismic loads presented in Table 5 for the western section are consistent with those provided by the current MBIE Module 1 (2021a) guideline.

7.4 Liquefaction and Cyclic Softening

Liquefaction is a phenomenon where saturated loose to medium-dense sands and low plasticity silts experience a rise in porewater pressures during strong shaking. This results in the loss of strength and stiffness of liquefied soils and consequent large deformations due to the development and subsequent dissipation of excess pore water pressures.

Cyclic softening can occur within cohesive materials under earthquake loading. This will cause the shear strength of cohesive soils to reduce under successive cyclic action.

7.4.1 Liquefaction Susceptibility

Based on the recommendations by Boulanger and Idriss (2014), soils are generally divided in two categories in terms of liquefaction susceptibility based on the plasticity index:

- Soils that behave in a 'sand-like' manner under seismic shaking and are susceptible to classic liquefaction. These soils generally exhibit a plasticity index (PI) of less than 7.

- Soils that behave in a 'clay-like' manner under seismic shaking and are susceptible to cyclic strain softening. These soils generally exhibit a plasticity index (PI) of great than 12.

A summary of the Atterberg Limits testing on two representative samples from the alluvium in BH1 is presented in Table 6 below.

Table 6: Summary Atterberg Limits test results in BH1

Sample Depth (m BGL)	Sample Description*	Liquid Limit (LL)	Plastic Limit (PL)	Plasticity Index (PI)	Natural Water Content (%)
2.0 – 2.45	Sandy SILT with trace clay	40	NP**	NP**	29.8
5.0 – 5.45	SILT with some clay and minor sand	39	25	14	34.2

The testing suggests the 'sandy silt interbeds' (sample between 2.0m – 2.45m bgl) to be generally low in plasticity or non-plastic, consistent with the borehole log descriptions. However, the 'silty CLAY/clayey SILT' interbeds (sample between 5.0m – 5.45m bgl) tend to exhibit a high Plasticity Index value of 14 and therefore is not considered susceptible to liquefaction.

7.4.2 Assessment Methodology

A quantitative liquefaction assessment has been carried out using the CLiq software (Version 3.0.2.4) based on the methodology outlined by Idriss and Boulanger (2014) method. The assessment has utilised the SPT data within the alluvium in BH1. A SPT hammer efficiency of 91% was adopted based on the calibration information provided by the drillers.

The fine contents have been estimated based on the limited PSD testing on selected samples from BH1 as well as the proportion of fines in the borehole log descriptions in accordance with the NZGS (2005) guideline. The adopted fines contents are presented on the analysis outputs in Appendix E. A sensitivity assessment has been carried out by reducing the input fines contents by 20% to assess the sensitivity of results to input fines contents.

A groundwater level of 2m bgl has been adopted based on the piezometer monitoring results to date. A sensitivity check has also been carried out based on a higher groundwater level of 1m bgl.

7.4.3 Results

The assessment results suggest the following:

- Liquefaction or cyclic softening is not expected under a SLS shaking event (i.e. 1 in 25-year event).
- Liquefaction or cyclic softening is not anticipated under a ULS shaking event (i.e. 1 in 500-year event).

Selected liquefaction assessment outputs are presented in Appendix E.

The undrained shear strength adopted for the alluvium (Unit 2) in the stability assessments is reasonably conservative and allows for potentially cyclic softening in the deeper clay-like layers below groundwater table.

The sensitivity checks based on lower fine content values as well as the elevated groundwater level did not have an appreciate effect on the analyses results. Please note the analysis has been based on the SPT's within BH1. Given the highly interbedded nature of

the alluvial deposits, the SPTs may not capture the presence of thin liquefiable layers. The BH1 logs indicate the alluvium to consist of high plasticity silty CLAY (around 60% of the total layer thickness) and therefore any consequences of liquefaction of thin sand-like interbeds below groundwater table are going to be minor due to the presence of a cohesive crust.

8 Geotechnical Considerations

8.1 Global Stability

Preliminary global stability assessments have been carried out under static, seismic and high groundwater conditions using the GeoStudio software Slope/W (2022 Version). The analyses have been carried out for the proposed landfill expansion site, the proposed Transfer Station site and the existing landfill site. The assessment results are discussed below.

8.1.1 Landfill Expansion Stability

A preliminary global stability the proposed landfill expansion has been carried out under static, seismic and high groundwater conditions using the GeoStudio software Slope/W (2022 Version). The analyses have been based on two representative sections across the new landfill as described below. Indicative alignments of the sections are shown on the preliminary drawings in Appendix B.

- Section 1 in the 'east to west' direction.
- Section 2 in the 'north to south' direction.

The proposed landfill consists of 1(V): 4(H) side batters, with 1(V): 3(H) side slopes excavated into rock to form the landfill cell floor.

The minimum required Factors of Safety (FoS) in line with the industry practice are as follows:

- Minimum FoS of 1.5 and 1.25 under the 'static – long-term' and 'static – high groundwater level' conditions, respectively.
- Minimum FoS of 1.2 for the 'seismic' event, with allowance for seismically induced displacements if $FoS < 1.2$. These displacements have been estimated based on the methodologies by Jibson (2007), Bray & Travararou (2007) and Ambraseys & Menu (1988), as recommended by the Bridge Manual.

A summary of the global stability assessment results is presented in Table 7 below. Selected Slope/W outputs are presented in Appendix F of this report.

There is a very low risk of global stability of the proposed landfill extension toward the south (Clutha River / Mata-Au) due to the presence of bedrock at very shallow depth below the ground between the landfill and the highway. Therefore, the assessment is focused on the stability of the landfill batters.

The assessments indicate the minimum factors of safety are achieved under the static case and the seismically induced slope movements are small and insignificant.

Table 7: Summary preliminary global stability assessment results

Analysed Section	Cases	Slope/W Factor of Safety	Minimum Target Factor of Safety	Yield Acceleration / Seismically-induced Displacements (mm)	Comments
Section 1 (east to west)	Static – Long Term	3.0	1.5	N/A	Long-term GWL of 2m bgl.
	Static – Short Term (High GWL)	3.0	1.25	N/A	Elevated GWL of 1m bgl.
	Seismic - SLS	2.5	1.0	None	Pseudo-static PGA of 0.04g.
	Seismic - DCLS	1.6	1.0	None	Pseudo-static PGA of 0.17g.
Section 2 (north to south)	Static – Long Term	2.8	1.5	N/A	Long-term GWL of 2m bgl.
	Static – Short Term (High GWL)	2.8	1.25	N/A	Elevated GWL of 1m bgl.
	Seismic - SLS	2.3	1.2	None	Pseudo-static PGA of 0.04g. Undrained parameters for Unit 2 govern.
	Seismic - DCLS	1.05	1.2	Negligible	Pseudo-static PGA of 0.17g. Undrained parameters for Unit 2 govern. Displacements are expected to be negligible of PGA of 0.23g is adopted (MBIE model 1)

8.1.2 Existing Landfill Stability

The stability of the existing landfill and the western section of the site has been analysed based on a typical cross section through the landfill and in the north-east / south-west direction (refer to Appendix B for the indicative alignment of the section). The assessment has been based on the extrapolated ground conditions and conservatively does not allow for any stabilising effect from the existing cut off wall. A summary of the assessment results is presented in Table 8 below.

Table 8: Summary of the stability assessment results for the existing landfill

Cases	Slope/W Factor of Safety	Minimum Target Factor of Safety	Yield Acceleration / Seismically-induced Displacements (mm)	Comments
Static – Long Term	2.1	1.5	N/A	Long-term GWL of 2m bgl at the base of landfill (i.e. pond locations)
Static – Short Term (High GWL)	1.7	1.25	N/A	Long-term GWL at ground level at the base of landfill also approximately 5m below landfill top.
Seismic - SLS	1.3	1.2	None	Pseudo-static PGA of 0.06g. Undrained parameters govern for Unit 2.
Seismic – DCLS	0.7	1.2 (Except where limited displacement is acceptable)	0.08 g / (10 – 90mm)	Pseudo-static PGA of 0.23g. Undrained parameters govern for Unit 2.

The preliminary assessment indicates the existing landfill site achieves the minimum required factors of safety under the static case. While the factor of safety under DCLS seismic is less than the 1.2 normally accepted the seismic displacements are small (<100mm) and may be acceptable. Under a DCLS event, displacements of the bund may occur with some associated cracking of the capping soils. However, these displacements are not expected to be sufficient to release contaminated landfill soils and may cause some cracking of the capping soils that may need to be reprofiled/topped up.

8.1.3 Transfer Station Cut Slope Stability

Excavations into an existing cut slope are proposed to allow the construction of the Transfer Station and associated facilities towards the centre of the site. A preliminary assessment has been carried out to assess the stability of the cut slope excavated at 1(V): 2(H) based on a representative cross section (refer Appendix B). A summary of the assessment results is presented in Table 9 below.

Table 9: Summary cut slope stability assessment results

Cases	Slope/W Factor of Safety	Minimum Target Factor of Safety	Yield Acceleration / Seismically-induced Displacements (mm)	Comments
Static – Long Term	2.9	1.5	N/A	Long-term GWL of 2m bgl at the toe of slope.
Static – Short Term (High GWL)	2.8	1.25	N/A	Elevated GWL of 1m bgl.
Seismic - SLS	2.6	1.2	None	Pseudo-static PGA of 0.04g. Drained parameters govern.
Seismic - DCLS	2.0	1.2	None	Pseudo-static PGA of 0.17g. Drained parameters govern.

The assessment indicates that 1(V): 2(H) cut slopes are stable under the static and seismic cases. This is generally supported by the inspection of existing cut slopes across the site. The seismic displacements are expected to be negligible even if the PGA of 0.23g is adopted under the DCLS case.

8.2 Long-Term Settlements

The surficial soils overlying bedrock generally consist of a thin layer of topsoil across the entire site and alluvial deposits across the western section of the site. Topsoil is typically less than 1m thick and the thickness of alluvium is expected to be variable, with a thickness of up to 6m proven in BH1.

The currently proposed landfill facilities, namely the RRC and Transfer Station, are mainly concentrated towards the landfill entrance at the southern end, where continuous alluvial deposits are not anticipated. There, any settlements affecting these light-weight structures are expected to be small (typically less than 20mm). The proposed landfill floor is also underlain by bedrock.

Please note that if encountered, any topsoil or localised alluvial deposits should be removed from the landfill floor or building footprints to minimise the risk of differential settlements.

If structures are considered on the existing landfill or in the proposed western landfill in the future, these may be subject to excessive settlement. Detailed settlement analyses should be carried out to assess the magnitude and rate of settlement. Additional investigations and/or laboratory testing may also be required to inform the assessment of appropriate settlement parameters.

8.3 Foundation Design Inputs

We understand that several light-weight structures are proposed near the landfill entrance at the southern end. Even though the actual forms of these structures are not certain at this stage of the project, these structures are expected to be single storey and light weight. Given the anticipated shallow depths to bedrock at the locations of the proposed buildings and there are no proposed buildings on the existing landfill, shallow foundations such as isolated pad footings or slabs are considered appropriate.

The forms of foundations should be confirmed during the Detailed Design stage of the project following the confirmation of locations and loading from the structures.

8.4 Existing Cut-off Wall Performance

As described in Section 2.1, an approximately 46m long sheet pile cut-off wall is currently employed to contain leachate from the existing landfill. Limited information about the cut-off wall is currently available. Due to difficulties with physically accessing the wall due to its depth below the bund, no materials testing has been carried out to date to determine the condition of the existing sheet pile sections.

Given the sheet pile has been in ground for almost 28 years, it is likely that a degree of corrosion loss of the steel sections has occurred to date. A preliminary assessment of the likely level of corrosion in the sheet pile and therefore the residual life of the structure has been carried out through discussions with a WSP Materials Expert. The assessment is based on the following considerations:

- Based on our discussions with the Materials Expert, the likely corrosion rates for the fully embedded driven piles in non-aggressive soils are typically less than 10 micron-m/year. The historic pH testing carried out by Royd Consulting Limited on three samples suggested pH values ranging between 6 – 8, suggesting the soils are non-corrosive. This is further supported by the visual inspection of the cores recovered from the boreholes (in particular BH1), which do not suggest the presence of organics or potentially aggressive soils.
- Pitting corrosion is likely to be the governing type of corrosion affecting the sheet piles. Pitting is a localised form of corrosion resulting in the formation of localised holes or cavities in the materials. Based on the review of available literature, the average rate of pitting corrosion is typically considered to be 5 times the average corrosion rate. On this basis, the pitting corrosion rate is 50 micron-m/year.
- Based on a conservative assumption that the pitting occurs at same locations on both sides of the sheet pile (i.e., total pitting corrosion loss of 0.1mm/year) and considering the wall has been in ground for around 28 years, the total section loss due to pitting is assessed to be up to 3mm.
- The sheet pile section type is not specified on the historic drawings, except for the suggested section width of 0.4m. Based on our knowledge of sheet pile products, the sheet pile section is likely an AZ-800 section. The various AZ-800 sections have thicknesses ranging between 8.5mm and 11mm. Assuming the section had the thickness of 8.5mm as the worst-case scenario, the expected residual thickness of the section is currently expected to be 5.5mm. This means the existing wall is expected to have a residual life of over 55 years.

Based on the conservative approach above, we consider the risk of pitting corrosion having resulted in holes in the existing wall is very low. Contamination testing on samples from the

groundwater wells downgradient of the cut-off wall also indicate a relatively high pH values in the samples (typically ranging between 6 – 8), resulting in low levels of corrosion.

The available drawings indicate the sheet piles were driven to refusal on the weathered or fresh bedrock. The assessments to date (section 6.3) have indicated a wide range of permeability of between 10^{-9} to 10^{-4} m/s in the weathered rock. This is thought to result from variability in jointing with the higher values likely to be in highly jointed rock and the lower values possibly in fresh rock.

No construction records of the low permeability clay barrier constructed at the two ends of the cut-off wall (beyond the sheet piles) is available. Based on above, the potential for leachate escaping through the bedrock below the cut-off wall or through the clay barrier at the two ends cannot be discounted. Based on discussions with the WSP Hydro-geologist, we understand that leachate has potentially been identified through groundwater monitoring of the historic wells and BH1 downgradient of the cut-off wall.

Given the consequences of leachate escaping through the landfill, it is recommended that monitoring the groundwater wells downgradient of the wall to be continued.

8.5 Suitability of site Soils for Reuse as a natural Soil Liner

The site is underlain by a thin layer of topsoil and alluvial deposits, overlying bedrock. The alluvial deposits encountered in BH1 are highly interbedded and mixed and are unlikely to have sufficiently low permeabilities to be suitable for use as liner based on the borehole descriptions. The extent of the alluvial deposits is also relatively limited to the south-west section of the site, and the use of these soils would require extensive excavations and sorting on site. The completely weathered bedrock (Unit 3a) may potentially be a suitable source to be used in the liner or capping system, however this layer is quite thin and localised and requires considerable testing and quality control.

Based on the above, low permeability clays to achieve the target permeability levels (in the order of 10^{-8} m/s) to be used in the liner or the capping layer systems need to be imported to site.

A suitable and adequate source of clay have not been identified from onsite but could be considered from an off-site location. We are not aware of a suitable location. Also, significant investigation and testing could be required to identify and prove an adequate source and then a reasonable extensive programme of quality control laboratory testing would need to be completed during construction to ensure the required permeability is achieved. The natural liner soils would be moisture sensitive, limiting construction to dry periods and tight dimension controls would be required during construction as well as *in-situ* permeability testing.

8.6 Proposed Liner for Landfill Expansion

Given that suitable site-won soils to be incorporated into the liner system are not available, a needle punched Geosynthetic Clay Liner (GCL) will be required to reduce the thickness of low permeability clays in the liner system. The proposed liner configuration has the following main components:

- Placement and compaction of suitable clays as part of the liner system. The compacted clay liner would have a nominal thickness of 600mm at the required permeability of around 1×10^{-8} m/s.
- A needle punched bentonite GCL liner.
- 300mm thick layer of compacted confining soil over the GCL.
- Leachate drainage system.
- The subgrade will need to be cut to a smooth profile and a protection layer (e.g. sand or other fine soils) is likely to be required under and possible over the liner.

8.7 Liner Settlements

The proposed liner will be placed over the existing bedrock across the eastern section of the proposed landfill. However, Stages 4 and 5 of the proposed landfill expansion (around the western and north-western sections) will involve the placement of fill and refuse over the existing landfill batters and top, with a liner between the new and existing waste. The additional fill on top of the existing landfill is in the order of 10m high based on the existing cross sections. This is likely to result in settlements of the existing fill and may cause damage to the liner system due to differential settlements. The risk of rupture of the liner resulting in leachate escaping towards the Clutha River / Mata-Au is considered low due to the following reasons:

- The site topography suggests that in the event of liner rupture, any leachate flow is expected to drain quickly to the base liner and the leachate collection system.
- Construction of Stages 4 and 5 are currently estimated to be 20 years away, which will give adequate time for the landfill to settle and provide an indication of the performance of the landfill.

A specific design of a suitable liner system will be required at that stage to address that the risk of rupture is minimised, and leachate is adequately collected and discharged in the event of localised rupture.

9 Earthworks Considerations

A summary of the earthworks considerations relevant to the landfill development is presented below.

9.1 Overview

The expected earthworks operations for the landfill expansion generally includes the following:

- Excavations in the area to the east and south of the existing landfill to create the proposed landfill floor. Some level of excavation has been completed to date in some areas.
- Cut and fill to form the access roads and proposed building platforms. Extensive excavations into an existing cut slope would be required to allow the construction of Transfer Station and associated structures.
- Liner protection layer placement, if required
- Liner construction.
- Landfill capping, including intermediate capping layers.
- Landscaping on completed landfill cells.

9.2 Cut and Fill Batters

Based on the investigation results and preliminary mapping, the following preliminary permanent cut batters are proposed for this stage of the project:

- 1(V): 2.5(H) cut slopes in Alluvium (**Unit 2**).
- 1(V): 1.5(H) in Caples Terrane bedrock (**Unit 3**), with 1(V): 2(H) cut slopes in more weathered rock encountered (such as Section 2 of the cut slope).

Minor filling would be required to form the access track and the building platforms. The fill should consist of granular free-draining aggregate (AP65 or similar approved by the Engineer), compacted in thin lifts.

Given the highly fractured nature of the rock, excavations into rock are anticipated to be generally easy as currently carried out on site. Rock breakers may be required in localised areas, where more fresh rock is encountered.

Any topsoil or soft alluvial deposits should be removed from the base of the slopes, subject to the approval of the Engineer.

9.3 Material Re-use

The recent investigations carried out across the site indicate the thin layer of topsoil as well as alluvial deposits across the western half of the site. Given the soft nature of topsoil as well high fines content and interbedded nature of the alluvial deposits, these soils are not considered suitable to be used as structural or bulk fill. The excavated soils may however be used for landscaping purposes across the site.

Excavated weathered rock may be used as bulk fill subject to approval of the Engineer and provided they can be well compacted in thin layers. Laboratory testing will be required to demonstrate the suitability of rock to be used as fill.

10 Conclusions

The main conclusions from the preliminary geotechnical assessments are summarised below;

- Based on the investigation results and our knowledge of site geology, the site is generally underlain by a thin layer of topsoil and alluvium, overlying Caples Terrane bedrock. The alluvium is thin to absent across the western section, but inferred to be continuous across the eastern section, with thickness of up to 6m proven in BH1.

The recent investigations and preliminary geological mapping suggest the strength and weathering of the bedrock is relatively consistent across the site and is highly jointed. The rock typically consists of 'Highly to moderately weathered, very weak to weak sandstone/siltstone' overlying 'slightly weathered to fresh, moderately strong to strong sandstone/siltstone'.

- Monitoring of the standpipe piezometers installed in BH1 to BH6 and BH10 to date indicates the long-term groundwater levels generally lie within the alluvial deposits or weathered bedrock at depths ranging between 1m to 4m bgl (or 6m to 20m RL). The preliminary analyses have considered elevated groundwater levels during heavy rainfall events.
- Caples Terrane bedrock is expected at shallow depths (typically < 1m bgl) across the eastern section of the site, resulting in the subsoil class for this section is 'B – Rock' (in accordance with NZS1170.5). Due to the presence of alluvial deposits, bedrock is anticipated at greater depths across the western section of the site (up to approximately 7m bgl in BH1), resulting in the site subsoil class is 'C – Shallow Soils'.
- Due to the shallow depths to bedrock across the eastern section, liquefaction or cyclic softening is not anticipated. A quantitative liquefaction assessment based on the SPT data within BH1 indicates that liquefaction nor cyclic softening of the alluvial deposits below the groundwater table are not anticipated under seismic SLS or ULS shaking events.
- Preliminary global stability assessments using the Slope/W software indicate the proposed landfill faces at 1(V): 4(H) achieve the acceptable factors of safety under the static and seismic cases. A moderately conservative assessment of the stability of the existing landfill site ignoring any pinning effect from the existing cut off wall also indicates that the factors of safety under the static and seismic SLS cases are achieved and minor displacement of the landfill face of up to 100mm in a DCLS event but this is considered to be acceptable.
- A part of the construction of Stages 4 and 5, the new landfill will be constructed over the existing landfill, with the construction anticipated to be around 20 years away. The design of a suitable liner system for these sections should consider the potential settlements and ensure any leachate in the event of localised liner rupture is adequately collected and discharged.
- Given the shallow depth to bedrock and the limited thickness of the soil cover across the majority of the site, long term settlements under the loads from the proposed structures or fill slopes are anticipated to be small and occur immediately. The proposed landfill facilities are concentrated towards the existing landfill entrance to the south of the site, where thick

layers of alluvium are not anticipated. This assumes future buildings are not located on the existing landfill.

- The alluvial deposits across the site are highly variable and are not likely to achieve the low permeabilities required for use as liner. Therefore, suitable low permeability clays need be imported to site for use as liner and capping layers (including intermediate) of the proposed landfill. Excavated topsoil and alluvium may be used for landscaping purposes.
- The existing landfill is not lined and relies on an existing sheet pile cut off wall immediately to the south to contain leachate. An assessment of the likely corrosion of the existing sheet pile cut off wall indicates the sheet pile section is likely to have a residual life exceeding 50 years and the risk of holes or cavities being present due to pitting corrosion is considered to be low.
- Monitoring of the existing groundwater wells downgradient of the cut-off wall to date has detected leachate. Based on the existing data, the likelihood of leachate escaping through the highly fractured bedrock below the cut-off wall or through the low permeability clay barriers at the two ends cannot be discounted.
- Based on the ground conditions, preliminary safe cut batters of 1(V): 1.5(H) and 1(V): 2(H) are proposed for weathered bedrock and 1(V): 2.5(H) are proposed for alluvium.

Any fill slopes should comprise well compacted granular fill (AP65 or similar approved) at slopes not exceeding 1(V): 2(H).

11 Recommendations for Next Stage

The main recommendations for the next stage of the project (subject to the final layout) are presented below.


1. Intrusive investigations and preliminary geological completed across the site to date provide a good overview of the variability of ground and groundwater profiles across the site. However, additional investigations or mapping, in particular in the area to the south-west of the site, may be required dependent on the final layout of the proposed development. If these investigations are warranted, these may take the form of boreholes or cone penetration tests, or detailed geological mapping.
2. We recommend the ongoing monitoring of the piezometers to be carried out to assess the variability of groundwater levels.
3. Given the condition of the sheet pile cut off wall cannot be visually confirmed on site, we recommend ongoing monitoring of the water bores downgradient of the cut off wall by an experienced hydrogeologist to identify trends of leachate escape.
4. The design of the new landfill for Stages 4 and 5 should consider the risk of settlements and potential damage to the liner. The design should allow for measures to capture and discharge leachate in the event of localised rupture.
5. Subject to the final locations and arrangement of the buildings, geotechnical inputs may be required for the design of foundations for such structures.

12 References

- Ambraseys, N and J. M. Menu (1988). Earthquake-induced Ground Displacements.
- ASTM, 2011. ASTM D1586-11, Standard Test Method for Standard Penetration Test (SPT) and Split-Barrel Sampling of Soils. ASTM International, West Conshohocken, PA.
- Bray, J. D., & Travasarou, T. (2007). Simplified procedure for estimating earthquake-induced deviatoric slope displacements. *Journal of geotechnical and geoenvironmental engineering*, 133(4), 381-392.
- Idriss, I.M., & Boulanger R.W., (2014). Soil Liquefaction during Earthquakes: CPT and SPT based Liquefaction Triggering Procedures, University of California Davis, Report No. UCD/CGM 14/01.
- Jibson, R. W. (2007). Regression models for estimating co-seismic landslide displacement. *Engineering geology*, 91(2-4), 209-218.
- Ministry of Business, Innovation & Employment (MBIE), 2021a, *Earthquake geotechnical engineering practice – Module 1. Overview of the guidelines*.
- Mortimer, N., (2004). New Zealand's Geological Foundations, Gondwana Research, Volume 7, Issue 1, Pages 261 – 272.
- New Zealand Active Faults Database. Institute of Geological and Nuclear Sciences (GNS) Ltd. Accessed 28/03/2023.
- New Zealand Geotechnical Society (NZGS), 2005, *Field Description of Soil and Rock*.
- Qian X, Koerner R, Gray D (2002). *Geotechnical Aspects of Landfill Design and Construction*. Prentice-Hall Inc., New Jersey, USA.
- Royd Consulting Limited (1994). 'A Report of Site Investigations at the Mount Cooee Landfill', dated May 1994.
- Waka Kotahi NZ transport Agency (2022). *Bridge Manual (SP/M/022)*, Third Edition.
- WasteMINZ, 2022. *WasteMINZ Technical Guidelines to Land 2022*.
- WSP (March 2023). 'Mt Cooee Landfill Development Plan and Resource Recovery Centre – Geotechnical Factual Report' by WSP dated 31 March 2023, Revision 2.
- WSP (April 2023). 'Mt Cooee Landfill Development Plan – Sheet Pile Cut-off Review Report' by WSP dated 5 April 2023.

Appendix A

Site Plan




- LEGEND**
- Proposed New Shallow Groundwater Well
 - Proposed Shared Hydro/Geotech Borehole
 - Proposed Geotechnical Boreholes
 - ⊗ Existing Groundwater Monitoring Well
 - ⊗ Sediment Pond Monitoring Site
 - ⊗ Surface Water Monitoring Site
 - Oxidation Ponds
 - ⊗ Pump Station
 - ⊗ Royds Boreholes (1993)
 - Proposed Fill Area Expansion

ISSUED FOR COMMENT
DRAFT

- NOTES**
1. Map image: © OpenStreetMap (and) contributors, CC-BY-SA Eagle Technology, Land Information New Zealand, GEBCO, Community maps contributors
 2. Schematic only, not to be interpreted as an engineering design or construction drawing.

COPYRIGHT

Information contained in this drawing is the copyright of WSP New Zealand Limited. Unauthorised use or reproduction of this plan either wholly or in part without written permission infringes copyright. © WSP New Zealand Limited




CLIENT CLUTHA DISTRICT COUNCIL			
PROJECT MT COOEE LANDFILL DEVELOPMENT PLAN			
TITLE MT COOEE PROPOSED DRILLING PLAN			
CONSULTANT	YYYY-MM-DD	2022-07-06	
	PREPARED	KC	
PROJECT NO.	REPORT	REV.	FIGURE
6-CO082.00	N/A	N/A	01

IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN ON THE SHEET, THE SHEET SIZE HAS BEEN ADOPTED FROM A3




Appendix B Preliminary Layout Plan



- NOTES**
1. ALL SIGNS TO BE IN ACCORDANCE WITH THE TRAFFIC CONTROL DEVICES MANUAL. PAINT MARKINGS TO BE IN ACCORDANCE WITH THE LATEST VERSION OF THE NZTA MANUAL OF TRAFFIC SIGNS AND MARKINGS PART I AND PART II.
 2. ALL EXISTING SERVICES ARE SHOWN INDICATIVELY ONLY.
 3. COORDINATES IN TERMS OF NORTH TAIERI CIRCUIT 2000. LEVELS ARE IN TERMS OF BALCLUTHA FUNDAMENTAL.
 4. REFER TO THE WSP GEOTECHNICAL FACTUAL REPORT FOR THE LOCATION OF GEOTECHNICAL INVESTIGATION POINTS.

LEGEND

	EXISTING EDGE OF SEAL
	NEW CENTERLINE
	NEW EDGE OF SEAL
	EXISTING FENCE
	NEW OR RELOCATED FENCE
	TOP OF CUT BATTER
	EXISTING LEACHATE DRAIN
	EXISTING FOUL SEWER LINE
	EXISTING OPEN DRAIN
	EXISTING WATER LINE
	EXISTING SUBSOIL DRAIN
	PROPOSED LEACHATE DRAIN
	PROPOSED FOUL SEWER LINE
	PROPOSED STORMWATER
	EXISTING CULVERT
	PROPOSED SUBSOIL
	CADASTRAL BOUNDARY
	PROPOSED LANDFILL
	NEW SEAL
	PROPOSED CONCRETE PAD
	OPERATIONS AREA
	PROPOSED LANDSCAPING
	PROPOSED RESOURCE CENTRE YARD
	POWER POLES
	PROPOSED SUMP
	PROPOSED MANHOLE



NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

WORK IN PROGRESS
PRINTED 4/04/2023 3:13:33 pm

REVISION	AMENDMENT	APPROVED	DATE



wsp
Invercargill Office
+64 3 211 3580
PO Box 647
Invercargill 9840
New Zealand

CIVIL

SCALES		ORIGINAL SIZE
1:750@A1	1:1500@A3	A1
DRAWN	DESIGNED	APPROVED
AUTHOR	DESIGNER	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD

PRELIMINARY

PROJECT
CLUTHA DISTRICT COUNCIL
KAITANGATA HIGHWAY BALCLUTHA
MT COOEE LANDFILL DEVELOPMENT

TITLE
LANDFILL, TRANSFER STATION & RESOURCE RECOVERY CENTRE
OVERALL SITE PLAN

WSP PROJECT NO. (SUB-PROJECT)
6-CO082.00

SHEET NO.
C101

REVISION
A



NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

WORK IN PROGRESS
PRINTED: 28/08/2023 12:03:55 pm

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		




wsp
Auckland Office
+64 9 355 9500
PO Box 5848
Auckland 1141
New Zealand

CIVIL

SCALES		ORIGINAL SIZE
N.T.S		A1
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD
PRELIMINARY		

PROJECT	CLUTHA DISTRICT COUNCIL KAITANGATA HIGHWAY BALCLUTHA MT COOEE LANDFILL DEVELOPMENT
TITLE	LANDFILL EXPANSION OVERALL LANDFILL FLOOR DESIGN
WSP PROJECT NO. (SUB-PROJECT)	6-CO082.00
SHEET NO.	C200
REVISION	A



WORK IN PROGRESS

PRINTED: 28/03/2023 12:04:14 pm

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		



wsp
 Auckland Office
 +64 9 355 9500
 PO Box 5848
 Auckland 1141
 New Zealand

CIVIL

SCALES		ORIGINAL SIZE
N.T.S		A1
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD

PRELIMINARY


PROJECT
**CLUTHA DISTRICT COUNCIL
 KAITANGATA HIGHWAY BALCLUTHA
 MT COOEE LANDFILL DEVELOPMENT**

TITLE
**LANDFILL EXPANSION
 LANDFILL STAGE 01**

WSP PROJECT NO. (SUB-PROJECT)
 6-CO082.00

SHEET NO.
 C201

REVISION
 A



NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

WORK IN PROGRESS

PRINTED: 28/03/2023 12:04:36 pm

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		




Auckland Office
+64 9 355 9500

PO Box 5848
Auckland 1141
New Zealand

CIVIL

SCALES	ORIGINAL SIZE	
N.T.S	A1	
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD
PRELIMINARY		

PROJECT	CLUTHA DISTRICT COUNCIL KAITANGATA HIGHWAY BALCLUTHA MT COOEE LANDFILL DEVELOPMENT
TITLE	LANDFILL EXPANSION LANDFILL STAGE 02
WSP PROJECT NO. (SUB-PROJECT)	6-CO082.00
SHEET NO.	C202
REVISION	A



WORK IN PROGRESS

PRINTED 28/03/2023 12:04:57 pm

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		



wsp
 Auckland Office
 +64 9 355 9500
 PO Box 5848
 Auckland 1141
 New Zealand

CIVIL

SCALES	ORIGINAL SIZE	
N.T.S	A1	
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD
PRELIMINARY		

PROJECT
**CLUTHA DISTRICT COUNCIL
 KAITANGATA HIGHWAY BALCLUTHA
 MT COOEE LANDFILL DEVELOPMENT**

TITLE
**LANDFILL EXPANSION
 LANDFILL STAGE 03**

WSP PROJECT NO. (SUB-PROJECT)
 6-CO082.00

SHEET NO.
 C203

REVISION
 A



WORK IN PROGRESS

PRINTED: 28/03/2023 12:05:16 pm vulcan

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		



wsp
 Auckland Office
 +64 9 355 9500
 PO Box 5848
 Auckland 1141
 New Zealand

CIVIL

SCALES		ORIGINAL SIZE
N.T.S		A1
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD

PRELIMINARY


PROJECT
 CLUTHA DISTRICT COUNCIL
 KAITANGATA HIGHWAY BALCLUTHA
 MT COOEE LANDFILL DEVELOPMENT

TITLE
 LANDFILL EXPANSION
 LANDFILL STAGE 04

WSP PROJECT NO. (SUB-PROJECT)
 6-CO082.00

SHEET NO.
 C204

REVISION
 A



300 mm
200
100
50
0 10 mm



NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

WORK IN PROGRESS
PRINTED: 28/03/2023 12:05:32 pm

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		




wsp
Auckland Office
+64 9 355 9500
PO Box 5848
Auckland 1141
New Zealand

CIVIL

SCALES	ORIGINAL SIZE	
N.T.S	A1	
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD
PRELIMINARY		

PROJECT	CLUTHA DISTRICT COUNCIL KAITANGATA HIGHWAY BALCLUTHA MT COOEE LANDFILL DEVELOPMENT
TITLE	LANDFILL EXPANSION LANDFILL STAGE 05
WSP PROJECT NO. (SUB-PROJECT)	6-CO082.00
SHEET NO.	C205
REVISION	A



NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

Setions adopted for Slope Stability. Batter Slopes modified to 1(V): 4(H) as the maximum batter for slope stability assessments

WORK IN PROGRESS
PRINTED 5/04/2023 10:34:53 am

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		



wsp
Invercargill Office
+64 3 211 3580
PO Box 647
Invercargill 9640
New Zealand


CIVIL

SCALES		ORIGINAL SIZE
N.T.S		A1
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD
PRELIMINARY		


PROJECT	CLUTHA DISTRICT COUNCIL KAITANGATA HIGHWAY BALCLUTHA MT COOEE LANDFILL DEVELOPMENT
TITLE	LANDFILL EXPANSION SECTION OVERALL
WSP PROJECT NO. (SUB-PROJECT)	6-CO082.00
SHEET NO.	C206
REVISION	A

NOTE:
GROUND CONDITIONS ARE INDICATIVE
ONLY AND TO BE CONFIRMED ON SITE.

300 mm
200
100
50
0 10 mm



SECTION 01
SECTION BETWEEN CH: 0.00 AND 244.07



SECTION 02
SECTION BETWEEN CH: 0.00 AND 226.20

LEGEND:

- TOPSOIL (UNIT 1)
- LANDFILL STAGE 01
- LANDFILL STAGE 02
- LANDFILL STAGE 03
- LANDFILL STAGE 04
- LANDFILL STAGE 05
- HISTORIC LANDFILL
- ALLUVIAL (UNIT 2)
- HIGHLY TO MODERATELY WEATHERED GREYWACKE, VERY WEAK TO WEAK SANDSTONE/SILTSTONE (UNIT 3b)
- SLIGHTLY WEATHERED TO FRESH, MODERATELY STRONG TO STRONG SANDSTONE/SILTSTONE (UNIT 3c)
- PROPOSED TOP OF PIT
- EXISTING GROUND

NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

WORK IN PROGRESS
PRINTED 5/04/2023 11:00:41 am

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		



wsp
Invercargill Office
+64 3 211 3580
PO Box 647
Invercargill 9840
New Zealand

CIVIL


SCALES		ORIGINAL SIZE
A1 1:500, A3 1:1000		A1
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD

PRELIMINARY

PROJECT		SHEET NO.	REVISION
CLUTHA DISTRICT COUNCIL KAITANGATA HIGHWAY BALCLUTHA MT COOEE LANDFILL DEVELOPMENT		C207	A
TITLE			
LANDFILL EXPANSION SECTIONS STAGE 01 - STAGE 02			
WSP PROJECT NO. (SUB-PROJECT)			
6-CO082.00			

NOTE:
GROUND CONDITIONS ARE INDICATIVE
ONLY AND TO BE CONFIRMED ON SITE.


300 mm
200
100
50
0 10 mm
Vertical Scale



SECTION 03
SECTION BETWEEN CH: 0.00 AND 201.72

LEGEND:

- TOPSOIL (UNIT 1)
- LANDFILL STAGE 01
- LANDFILL STAGE 02
- LANDFILL STAGE 03
- LANDFILL STAGE 04
- LANDFILL STAGE 05
- HISTORIC LANDFILL
- ALLUVIAL (UNIT 2)
- HIGHLY TO MODERATELY WEATHERED GREYWACKE, VERY WEAK TO WEAK SANDSTONE/SILTSTONE (UNIT 3b)
- SLIGHTLY WEATHERED TO FRESH, MODERATELY STRONG TO STRONG SANDSTONE/SILTSTONE (UNIT 3c)
- PROPOSED TOP OF PIT
- EXISTING GROUND



SECTION 04
SECTION BETWEEN CH: 0.00 AND 266.42

NOTE:
THIS DRAWING IS TO BE REPRODUCED IN COLOUR

WORK IN PROGRESS
PRINTED 5/04/2023 11:01:45 am

REVISION	AMENDMENT	APPROVED	DATE
A	DRAFT FOR COMMENT		




wsp
Invercargill Office
+64 3 211 3580
PO Box 647
Invercargill 9840
New Zealand

CIVIL

SCALES		ORIGINAL SIZE
A1 1:500 , A3 1:1000		A1
DRAWN	DESIGNED	APPROVED
R.GOLDSMITH	R.GOLDSMITH	APPROVER
DRAWING VERIFIED	DESIGN VERIFIED	APPROVED DATE
VERIFIER	VERIFIER	YYYY-MM-DD

PRELIMINARY

PROJECT		SHEET NO.	REVISION
CLUTHA DISTRICT COUNCIL KAITANGATA HIGHWAY BALCLUTHA MT COOEE LANDFILL DEVELOPMENT		C208	A
TITLE			
LANDFILL EXPANSION SECTIONS STAGE 01 - STAGE 02			
WSP PROJECT NO. (SUB-PROJECT)			
6-CO082.00			



Appendix C Machine Borehole Logs and Photographs



Borehole No. BH1

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: 30m west of Kaitangata Hwy, south of oxidation ponds
 Mt Cooee Landfill, Balclutha

Coordinates: 1350038 E 4873817 N
 Ref. Grid: NZTM
 R.L.: Approx. 9 m
 Datum: NZ Vertical Datum 2016
 Depth: 11.6 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS		ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP	DEFECTS / NOTES / OTHER TESTS	CORE		DRILLING		INSTALLATION DETAILS	
					SPT N° VALUE	SPT BLOW COUNTS OR SHEAR VALUE						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD		CASING
Alluvium	TS TOPSOIL, grass, trace rootlets and trace fine quartz gravel. 0.40-0.50m - Woody organics present.											RC	80				50 mm Blank pipe (6.2 m L) with grout backfill
	Silty CLAY with trace gravel and rootlets, dark grey, homogenous. Soft to firm, moist, high plasticity. Gravel; coarse, subangular. Core loss.	8	1		6	3// 1/2/1/2						SPT	100				
	Sandy SILT, light brown to brown, homogenous. Firm, moist to dry, low plasticity, micaceous. Sand; fine.											RC	100				
	Silty CLAY with trace sand and gravel, light brown with dark grey and brown specks, homogenous. Firm, moist, high plasticity. Gravel; fine, subangular. Sand; fine to coarse. 1.50m - Orange mottle.										Lab: 1.8 - 3.0m PSD and Atterberg Limits	SPT	100				
	Sandy SILT, brown, homogenous. Firm, dry, low plasticity. Sand; fine. 1.80m - Becomes light brown.	2			5	2// 1/1/1/2						RC	100				
	Silty fine to coarse SAND with trace rootlets, brown, homogenous. Loose, moist, micaceous. Silt; low plasticity. Becomes light grey to grey with trace of orange mottles, homogenous. Dry to moist, non-plastic, micaceous.										2.85-3.00m - Broken during removal from core catcher	SPT	100				
		6	3		7	2// 1/2/2/2						RC	100				
	Silty CLAY with trace sand, light grey with orange mottles throughout, homogenous. Soft to firm, moist, high plasticity, micaceous. Sand; fine to medium. 3.50m - Becomes firm.											SPT	100				
	3.90m - Becomes light grey with trace orange mottles (less than above), homogenous.	4			6	2// 2/1/2/1						RC	100				
	Sandy SILT, light brownish grey, homogenous. Soft, non-plastic dry. Sand; fine to medium.										Lab: 4.4 - 6.1m PSD and Atterberg Limits	SPT	100				
Caples Terrane	Silty CLAY, light greenish grey, homogenous. Soft to firm, moist, high plasticity.	4	5		1	0// 0/0/0/1						SPT	100				
	5.45-5.65m - Becomes light greyish green with trace green sandy laminations. 5.65-6.00m - Green sandy lenses. Becomes greenish grey.											RC	100				
	Silty CLAY with trace gravel and sand, dark grey with orange mottles, homogenous. Very soft, moist to wet, high plasticity. Gravel; fine to coarse, subangular to angular. Sand; fine to medium, subangular to subrounded.											SPT	100				
	Slightly weathered, highly fractured, light brownish grey, fine fabric SANDSTONE; moderately strong; very closely spaced joints and white veins. Recovered as: sandy GRAVEL with some silt, light brown. Gravel and sand; fine to coarse, subangular.	2	7		60+	12// 14/46 for 75mm						RC	100				
	7.50-8.00m - Gravel becomes; fine to coarse, coarser gravel is angular to subangular, finer gravel is rounded to subrounded.											SPT	100				
	Slightly weathered, highly fractured, light bluish grey, fine fabric SANDSTONE; moderately strong; closely spaced joints and white veins. Recovered as: Fine to coarse GRAVEL with minor sand, light greyish brown. Very dense, well graded, non-plastic. Gravel; coarser gravel is angular to subangular, finer gravel is rounded to subrounded. Sand; medium to coarse, rounded.	8			60+	60 for initial 110mm		MS	SW			RC	100	0			
9.17-9.35m - Recovered as: fine to coarse GRAVEL with minor cobbles, light grey. Very dense, well graded. Gravel; subangular. Greywacke, mm-scale white veins. Cobbles: max 80mm.										Lab: 9.0 - 11.0m UCS testing 9.17-9.35m - Rock broken up by drilling. Any matrix appears to be lost due to drilling.	SPT	100	0				
	9			60+	60 for initial 105mm						RC	100	0				

Notes:
 SPT hammer energy ratio 91%
 Shared Hydro / Geotech borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 19/10/2022
 Finished: 20/10/2022
 Drilling Co.: McMillan Drilling
 Drilling Rig: Hanjin D&B-8D - track
 Logged by: C. Hall
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan	Coordinates: 1350038 E 4873817 N
Client: Clutha District Council (CDC)	Ref. Grid: NZTM Depth: 11.6 m
Project No.: 6-CO082.00	R.L.: Approx. 9 m Inclination: Vertical
Location: 30m west of Kaitangata Hwy, south of oxidation ponds Mt Cooee Landfill, Balclutha	Datum: NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH1.1
BH1 Box 1: 0.0m - 2.4m



Photo BH1.2
BH1 Box 2: 2.4m - 4.45m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Shared Hydro / Geotech borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 19/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 20/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan	Coordinates: 1350038 E 4873817 N
Client: Clutha District Council (CDC)	Ref. Grid: NZTM Depth: 11.6 m
Project No.: 6-CO082.00	R.L.: Approx. 9 m Inclination: Vertical
Location: 30m west of Kaitangata Hwy, south of oxidation ponds Mt Cooee Landfill, Balclutha	Datum: NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH1.3
BH1 Box 3: 4.45m - 7.0m



Photo BH1.4
BH1 Box 4: 7.0m - 9.35m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Shared Hydro / Geotech borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 19/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 20/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes

<i>Project:</i>	Mt Cooee Landfill - Development Plan	<i>Coordinates:</i>	1350038 E 4873817 N
<i>Client:</i>	Clutha District Council (CDC)	<i>Ref. Grid:</i>	NZTM <i>Depth:</i> 11.6 m
<i>Project No.:</i>	6-CO082.00	<i>R.L.:</i>	Approx. 9 m <i>Inclination:</i> Vertical
<i>Location:</i>	30m west of Kaitangata Hwy, south of oxidation ponds Mt Cooee Landfill, Balclutha	<i>Datum:</i>	NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH1.5
BH1 Box 5: 9.35m - 11.0m



Photo BH1.6
BH1 Box 6: 11.0m - 11.6m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
SPT hammer energy ratio 91%
Shared Hydro / Geotech borehole
Core loss placed at end of run by default
123mm OD Rotary Coring

Started: 19/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 20/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH1 (ROYDS)

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Near Clutha River Bridge
 Mt Cooee Landfill, Balclutha

Coordinates: Not established
 Ref. Grid: NZTM
 R.L.: Approx. 116.39 m
 Datum:
 Depth: 15 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE		DRILLING		INSTALLATION DETAILS	
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE							SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD		CASING
TS	TOPSOIL with some fine gravel.	116	1															
	Light grey moderate to widely jointed GREYWACKE, [TUAPEKA GROUP GREYWACKE] - weathered, fractured zone at top of layer - very hard - some quartz filled joints	114	2															
		112	3															
		110	4															
		108	5															
			6															
			7															
			8															
			9															

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ - WSP-OPUS2019_VERT1X.GDT - 30/3/23

Tuapeka Group Greywacke

Rotary open hole

Slotted pipe

Notes:
 Air Rotary drilling method. 150mm diameter.
 Taken from Royds Garden Ltd borehole records.

Started: 28/01/1994
 Drilling Co.:
 Logged by:

Finished: 28/01/1994
 Drilling Rig:
 Checked by:



Borehole No. BH1 (ROYDS)

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Near Clutha River Bridge
 Mt Cooee Landfill, Balclutha

Coordinates: Not established
 Ref. Grid: NZTM
 R.L.: Approx. 116.39 m
 Datum:
 Depth: 15 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE							SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING	
Tuapeka Group Greywacke	Light grey moderate to widely jointed GREYWACKE. [TUAPEKA GROUP GREYWACKE] - weathered, fractured zone at top of layer - very hard - some quartz filled joints(continued)	106																
		11																
		12																
		104																
		13																
	END OF BOREHOLE AT 15m	15																
		16																
		100																
		17																
		18																
		98																
		19																

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ - WSP-OPUS2019_VERT1X.GDT - 30/3/23

Notes:
 Air Rotary drilling method. 150mm diameter.
 Taken from Royds Garden Ltd borehole records.

Started: 28/01/1994
 Drilling Co.:
 Logged by:

Finished: 28/01/1994
 Drilling Rig:
 Checked by:



Borehole No. BH2

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: North of site, north side of railway
 Mt Cooee Landfill, Balclutha

Coordinates: 1350241 E 4873978 N
 Ref. Grid: NZTM
 R.L.: Approx. 16 m
 Datum: NZ Vertical Datum 2016
 Depth: 6 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS	
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE							SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING		BASE OF HOLE & WATER LEVEL
TS	TOPSOIL.																		
Alluvium	GRAVEL with minor sand, brownish grey. Loose. Gravel; fine to coarse, subrounded, sandstone. Clay/silt/sand matrix inferred washed away. 0.70m - Some matrix present at 0.7m Core loss.		1										RC	55	0	Rotary cored	PQ size wireline (85 mm nom. dia. core)	Cement seal	
	Gravelly CLAY with some silt and minor sand, brown. Homogenous, soft, moist, high plasticity. Gravel; fine to coarse, angular, well graded. Core loss.		2										RC	45	0				
Caples Terrane	Completely weathered grey and orange/brown, fine fabric SANDSTONE. Extremely weak. Recovered as: SILT with minor gravel and some sand and clay. Homogenous, stiff to very stiff, moist, low plasticity. Gravel; fine to medium, subangular. Sand; fine. Core loss.		3				EW	CW	EC				RC	80	0	Rotary cored	PQ size wireline (85 mm nom. dia. core)	50 mm slotted pipe (3.0 m L)	
	Moderately weathered greenish grey, fine fabric SANDSTONE. Very weak to weak.		4				W	SW	VC										
	Completely weathered grey and orangeish brown, indistinctly bedded SANDSTONE. Extremely weak. Residual soil recovered as: SILT with some clay. Homogenous, stiff to very stiff, moist, and low plasticity. Moderately weathered greenish grey, indistinctly bedded SANDSTONE. Very weak to weak.		5				EW	CW	EC				RC	100	30				
	END OF BOREHOLE AT 6m - Target Depth Reached		6				WV	HW	VC										
			7				W	MW	C										
			8																
			9																
			10																
			6																

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 Shallow groundwater well
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 18/10/2022
 Finished: 19/10/2022
 Drilling Co.: McMillan Drilling
 Drilling Rig: Hanjin D&B-8D - track
 Logged by: N. Ahern
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: North of site, north side of railway
 Mt Cooee Landfill, Balclutha

Coordinates: 1350241 E 4873978 N
Ref. Grid: NZTM **Depth:** 6 m
R.L.: Approx. 16 m **Inclination:** Vertical
Datum: NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH2.1
BH2 Box 1: 0.0m - 4.2m



Photo BH2.2
BH2 Box 2: 4.2m - 6.0m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 Shallow groundwater well
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 18/10/2022
Drilling Co.: McMillan Drilling
Logged by: N. Ahern

Finished: 19/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH2 (ROYDS)

Project: Mt Cooe Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Near gate to landfill
 Mt Cooe Landfill, Balclutha

Coordinates: Not established
 Ref. Grid: NZTM
 R.L.: Approx. 109.29 m
 Datum:
 Depth: 9.5 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE							SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING	
TS	TOPSOIL with some fine gravel.																	
Pleistocene Glacial Deposits	Grey brown mottle yellow brown sandy silty fine GRAVEL.	108	1															
Tuapeka Group Greywacke	Light grey moderate to widely jointed GREYWACKE. - Weathered, fractured zone at top of layer - Very hard - Some quartz filled joints	106	2															
		104	3															
		102	4															
		100	5															
			6															
			7															
			8															
			9															
			10															
	END OF BOREHOLE AT 9.5m																	

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ - WSP-OPUS2019_VERT1X.GDT - 30/3/23

Notes:
 Air Rotary drilling method. 150mm diameter.
 Taken from Royds Garden Ltd borehole records.

Started: 30/01/1994
 Drilling Co.:
 Logged by:

Finished: 30/01/1994
 Drilling Rig:
 Checked by:



Borehole No. BH3

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Western area of site, 15m north-east of Kaitangata Hwy
 Mt Cooee Landfill, Balclutha

Coordinates: 1350135 E 4873642 N
 Ref. Grid: NZTM
 R.L.: Approx. 11 m
 Datum: NZ Vertical Datum 2016
 Depth: 4.5 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS	
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE	ROCK STRENGTH					SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING		BASE OF HOLE & WATER LEVEL
TS	TOPSOIL.																	
Alluvium	SILT with some clay and minor sand, grey/dark brown, homogenous. Soft, moist, low plasticity. Sand; fine to medium. Clayey SILT with minor sand, light brownish orange. Homogenous, soft, moist, with low to medium plasticity. Sand; fine. 0.90-0.92m - Cobble of moderately weathered, light brown massive SANDSTONE. Weak. Completely weathered, brownish orange, fine fabric SANDSTONE. Extremely weak. Recovered as: sandy SILT with minor clay, brownish orange, homogenous. Stiff, dry to moist, low plasticity. Sand; fine to medium.		10				EW	CW	EC			RC	100					
Caples Terrane	Highly weathered orange/brown, fine fabric SANDSTONE. Very weak. Recovered as: sandy GRAVEL with some cobbles and minor silt and clay, homogenous. Gravel; fine to coarse, subrounded. Cobbles; max 100mm, subrounded. Sand; fine to coarse. Core loss.		2				VW	HW	EC		2.40-2.50m - Core broken during removal from catcher.	RC	65	0	Rotary cored			
Caples Terrane	Moderately weathered dark green/orange, fine fabric SANDSTONE. Weak. Orange staining on all joint faces. Recovered as: COBBLES with minor gravel. Cobbles; max 100mm, mostly subangular with some subrounded (due to drilling). Gravel; medium to coarse, subangular. Core loss.		3				W	MW	VC		3.00-4.30m - Possible weaker material washed out by drilling.	RC	80	0				
	END OF BOREHOLE AT 4.5m - Target Depth Reached		4.5															
			5															
			6															
			7															
			8															
			9															
			9.2															

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ - WSP-OPUS2019_VER11X.GDT - 30/3/23

Notes:
 Shallow groundwater well
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 11/10/2022
 Drilling Co.: McMillan Drilling
 Logged by: N. Ahern

Finished: 12/10/2022
 Drilling Rig: Hanjin D&B-8D - track
 Checked by: C. Parkes

<i>Project:</i>	Mt Cooee Landfill - Development Plan	<i>Coordinates:</i>	1350135 E 4873642 N
<i>Client:</i>	Clutha District Council (CDC)	<i>Ref. Grid:</i>	NZTM <i>Depth:</i> 4.5 m
<i>Project No.:</i>	6-CO082.00	<i>R.L.:</i>	Approx. 11 m <i>Inclination:</i> Vertical
<i>Location:</i>	Western area of site, 15m north-east of Kaitangata Hwy Mt Cooee Landfill, Balclutha	<i>Datum:</i>	NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH3.1
BH3 Box 1: 0.0m - 3.0m



Photo BH3.2
BH3 Box 2: 3.0m - 4.5m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
Shallow groundwater well
Core loss placed at end of run by default
123mm OD Rotary Coring

Started: 11/10/2022
Drilling Co.: McMillan Drilling
Logged by: N. Ahern

Finished: 12/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH4

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: South-east corner of site
 Mt Cooee Landfill, Balclutha

Coordinates: 1350398 E 4873540 N
 Ref. Grid: NZTM
 R.L.: Approx. 9 m
 Datum: NZ Vertical Datum 2016
 Depth: 5.5 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS		
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE	ROCK STRENGTH						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING		BASE OF HOLE & WATER LEVEL	
Caples Terrane	TOPSOIL with roots and grass.		0									0.15-3.70m - Assumed some fines or weaker seams were present but these have been washed away by drilling.	RC	53	0					
	Sandy GRAVEL with trace rootlets, light brown to grey. Loosely packed, well graded, non-plastic. Gravel; angular to subangular, greywacke. Sand; fine to coarse, subrounded. 0.50-0.80m - Gravel; subangular to subrounded. Coarse sand; subangular to angular. Core loss.	8	1										1.50-5.50m - Fracturing due to drilling	RC	40	0				
	Slightly weathered to moderately weathered, highly fractured, orangish brown, fine fabric SANDSTONE; extremely weak; extremely closely spaced tight white veins; extremely weathered defects. Recovered as: COBBLES with some gravel and trace silt and rootlets, orangey brown to grey. Cobbles and gravel; fine to coarse. Cobbles; max 100mm, subangular. Sand; fine to coarse, subangular to subrounded. Silt; dark grey, lensoidal. 2.20-2.40m - Trace pockets of dark grey silt. Core loss.	6	2					EW	MW	EC				RC	80	0				
	Slightly weathered to moderately weathered, highly fractured, dark grey SILTSTONE. Very weak, bedding is thinly laminated. Recovered as: Sandy GRAVEL with some cobbles and silt, dark grey with some orange and white veins. Sand; fine to coarse, angular to subangular. Gravel and cobbles; fine to coarse, subangular. Cobbles; max 60mm. Fines; non-plastic. Core loss.	4	3					VW	MW	EC				RC	100	0				
Slightly weathered, highly fractured, dark bluish grey, fine fabric SILTSTONE. Weak. Mm scale mostly closed and oxidised defects. Recovered as: COBBLES with some gravel and trace silt, dark bluish grey with orange staining. Cobbles and gravel; fine to coarse, subangular. Cobbles; max 150mm. Sand; fine to coarse, subangular to subrounded. 5.00m - Slickensides on one piece of gravel.	4	4					W	SW	VC		50 45	4.10m - J, 50° 4.20m - J, 45°	RC							
END OF BOREHOLE AT 5.5m - Target Depth Reached			5.5																	

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT_30/3/23

Notes:
 Shallow groundwater well
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 27/10/2022
 Finished: 27/10/2022
 Drilling Co.: McMillan Drilling
 Drilling Rig: Hanjin D&B-8D - track
 Logged by: C. Hall
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: South-east corner of site
 Mt Cooee Landfill, Balclutha

Coordinates: 1350398 E 4873540 N
Ref. Grid: NZTM
R.L.: Approx. 9 m
Datum: NZ Vertical Datum 2016
Depth: 5.5 m
Inclination: Vertical

PHOTOGRAPHS



Photo BH4.1
 BH4 Box 1: 0.0m to 3.8m



Photo BH4.2
 BH4 Box 2: 3.8m - 5.5m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 Shallow groundwater well
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 27/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 27/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH5

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Southern area of site, 80m north-east of Kaitangata Hwy
 Mt Cooee Landfill, Balclutha

Coordinates: 1350288 E 4873598 N
 Ref. Grid: NZTM
 R.L.: Approx. 7 m
 Datum: NZ Vertical Datum 2016
 Depth: 3 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS
					SPT N° VALUE	SPT BLOW COUNTS OR SHEAR VALUE	ROCK STRENGTH						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING	
TS	TOPSOIL with some grass and rootlets and minor quartz sand.		0															
Alluvium	Silty CLAY with trace sand, orangish brown, homogenous. Firm to stiff, moist, high plasticity. Sand: medium.		0.90									Lab: 0.4 - 1.1m PSD and permeability testing.	RC	100	0			
Caples Terrane	Silty CLAY with minor sand, light greyish orange with minor white specks and orange mottle, homogenous. Stiff, moist, high plasticity. 0.90m - Becomes orange. Soft to firm.		1				VW	HW	VC			Lab: 1.1 - 2.6m UCS testing.						
	Highly weathered, brownish orange, fine fabric indistinctly bedded SANDSTONE. Weak to very weak; orange defects. 1.20m - Becomes moderately weathered to slightly weathered.		2				SW											
	Moderately weathered, greenish grey, fine fabric indistinctly bedded SANDSTONE. Weak to very weak; orange staining along open defects.		3				W	MW	C	10°		2.15m - J, 10°	RC	100	17			
			4				SW	VC	10°		2.50m - J, 10°							
	END OF BOREHOLE AT 3m - Target Depth Reached		3									2.90-3.00m - Core broken during removal from catcher.						
			4															
			5															
			6															
			7															
			8															
			9															
			-2															

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 Shallow groundwater well
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 17/10/2022
 Drilling Co.: McMillan Drilling
 Logged by: C. Hall

Finished: 18/10/2022
 Drilling Rig: Hanjin D&B-8D - track
 Checked by: C. Parkes

<i>Project:</i>	Mt Cooee Landfill - Development Plan	<i>Coordinates:</i>	1350288 E 4873598 N
<i>Client:</i>	Clutha District Council (CDC)	<i>Ref. Grid:</i>	NZTM <i>Depth:</i> 3 m
<i>Project No.:</i>	6-CO082.00	<i>R.L.:</i>	Approx. 7 m <i>Inclination:</i> Vertical
<i>Location:</i>	Southern area of site, 80m north-east of Kaitangata Hwy Mt Cooee Landfill, Balclutha	<i>Datum:</i>	NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH5.1
BH5 Box 1: 0.0m to 2.2m



Photo BH5.2
BH5 Box 2: 2.2m to 3.0m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
Shallow groundwater well
Core loss placed at end of run by default
123mm OD Rotary Coring

Started: 17/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 18/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH6

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Middle of site, southwest of excavation
 Mt Cooee Landfill, Balclutha

Coordinates: 1350315 E 4873694 N
 Ref. Grid: NZTM
 R.L.: Approx. 21 m
 Datum: NZ Vertical Datum 2016
 Depth: 9.45 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE		DRILLING		INSTALLATION DETAILS	
					SPT N° VALUE	SPT BLOW COUNTS OR SHEAR VALUE	RC						TCR (%)	RQD (%)	DRILLING METHOD	CASING		BASE OF HOLE & WATER LEVEL
TS	TOPSOIL with some grass and rootlets, dark brown. 0.20m - Becomes orangish brown.																	
Caples Terrane	Moderately weathered, light brownish orange, highly fractured, SANDSTONE. Moderately strong. Recovered as: gravelly COBBLES with some sand. Cobbles; angular, max 100mm. Gravel; medium to coarse, angular. Core loss.	20			56	15// 10/13/15/18	MS	MW	VC				RC	73				50 mm blank pipe (1.0 m L)
	Highly weathered, light brownish orange, highly fractured SANDSTONE. Weak. Recovered as: Sandy GRAVEL with some clay, orangish brown. Gravel; fine to coarse, subangular. Fines; high plasticity.	2					W	HW	EC				SPT	100				
	2.30m - Re-drilled cobble. Core loss.												RC	38				
	Moderately weathered, light grey to dark grey, highly fractured SANDSTONE. Moderately strong. Recovered as: GRAVEL with some sand, light grey to dark grey. Gravel; fine to coarse, subangular. Core loss.	18.3			60+	17// 14/16/21/9 for 25mm	MS	MW	VC				SPT	100				
	Core loss.	4											RC	38				
	Completely weathered, greenish grey, fine fabric SILTSTONE. Extremely weak. Recovered as: clayey SAND with trace silt. Sand; fine to medium. Fines; high plasticity. 4.95-5.25m - Lenses of silty CLAY, greenish grey, homogenous. Soft, moist, high plasticity.	16.5			60+	15// 13/26/21 for 45mm	EW	CW	EC				SPT	100				
	Moderately weathered, greenish grey, highly fractured fine fabric, indistinctly bedded SANDSTONE. Weak. Recovered as: sandy GRAVEL with some clay, bluish green. Gravel; medium to coarse. Fines; high plasticity.	6			60+	15// 20/24/16 for 50mm	W	MW	C				RC	100				
	Slightly weathered greenish blue, massive SILTSTONE. Weak to moderately strong. 5.70-5.90m - Moderately weathered, highly fractured along defects. Defects; open or extremely closed spaced and closed.	6					MS	SW	EC				SPT	100	0			
	6.45-6.55m - Pockets of silty SAND with pockets of clay, bluish green, homogenous. Loose, non-plastic. 6.55-7.20m - Black stained defects throughout.	14						SW	C				RC	100	0			
	Moderately weathered greenish blue, fine fabric SILTSTONE. Weak; black stained defects. Recovered as: COBBLES with some gravel and silt. Cobbles and gravel; angular. Gravel; medium to coarse. 7.00-7.20m - Grades into completely weathered rock. 7.20-7.50m - Recovered as: sandy GRAVEL with some silt, dark greenish grey to black. Loose, non-plastic. Gravel; fine to coarse, subrounded Siltstone.	8			60+	36// 48/12 for 35mm		CW	EC				SPT	90	0			
8.25m - Becomes slightly weathered, minor fractures, weak to moderately strong. Defects; closed aperture. Grain size grading larger from Siltstone to Sandstone.	8					W	MW	C				RC	100	0				
8.75-9.00m - Recovered as: sandy GRAVEL with some silt, dark greenish blue, homogenous. Loose. Gravel; highly weathered. 9.00-9.45m - Recovered as: silty SAND, greenish yellow, homogenous. Soft to firm, low plasticity. Sand; fine to medium.	12			60+	19// 22/38 for 75mm		HW	EC				SPT	93	0				
END OF BOREHOLE AT 9.45m - Target Depth Reached																		

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ - WSP-OPUS2019_VER11X.GDT - 30/3/23

Rotary cored
PQ size wireline (85 mm nom. dia. core)

50 mm blank pipe (1.0 m L)
50 mm slotted pipe (1.5 m L)
Grout

Lab: 5.3 - 9.45m UCS testing.

Notes: SPT hammer energy ratio 91%
 Shared Hydro / Geotech borehole
 Waiting on core box photos to calculate RQD
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 12/10/2022
 Finished: 18/10/2022
 Drilling Co.: McMillan Drilling
 Drilling Rig: Hanjin D&B-8D - track
 Logged by: C. Hall
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Middle of site, southwest of excavation
 Mt Cooee Landfill, Balclutha

Coordinates: 1350315 E 4873694 N
 Ref. Grid: NZTM
 R.L.: Approx. 21 m
 Datum: NZ Vertical Datum 2016
 Depth: 9.45 m
 Inclination: Vertical

PHOTOGRAPHS



Photo BH6.1
 BH6 Box 1: 0.0m to 4.5m



Photo BH6.2
 BH6 Box 2: 4.5m to 6.8m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Shared Hydro / Geotech borehole
 Waiting on core box photos to calculate RQD
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 12/10/2022
 Drilling Co.: McMillan Drilling
 Logged by: C. Hall

Finished: 18/10/2022
 Drilling Rig: Hanjin D&B-8D - track
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: Middle of site, southwest of excavation
 Mt Cooee Landfill, Balclutha

Coordinates: 1350315 E 4873694 N
Ref. Grid: NZTM **Depth:** 9.45 m
R.L.: Approx. 21 m **Inclination:** Vertical
Datum: NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH6.3
 BH6 Box 3: 6.8m to 9.45m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ - WSP-OPUS2019_VER11X.GDT - 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Shared Hydro / Geotech borehole
 Waiting on core box photos to calculate RQD
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 12/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 18/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH7

Project: Mt Coeee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Eastern most corner of site, 20m south of railway
 Mt Coeee Landfill, Balclutha

Coordinates: 1350492 E 4873800 N
 Ref. Grid: NZTM
 R.L.: Approx. 25 m
 Datum: NZ Vertical Datum 2016
 Depth: 6 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS
					SPT N° VALUE	SPT BLOW COUNTS OR SHEAR VALUE	DEGREE						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING	
TS	TOPSOIL.																	
Caples Terrane	Moderately weathered light grey to light brown with orange mottle, fine fabric SANDSTONE. Weak to moderately strong. Recovered as: gravelly COBBLES with some sand. Cobbles and gravel; angular. Gravel; medium, subrounded.		24		60	31//34/26		W	MW	EC		0.20-6.00m - Fractures opened by drilling.	RC	75	0			Gravel Surrounding ground collapse
	0.20-0.70m - Coarse to fine gravel, sandy silty matrix inferred fines washed away. Core loss.		24															
	Highly weathered, light brown with orange mottle, highly fractured, fine fabric SANDSTONE. Strong. Recovered as: Gravelly COBBLES. Gravel and cobbles; angular.		21					S	HW	VC			RC	85	0			
	1.00-2.00m - Sand/silt matrix inferred washed away.		2															
	1.55m - Becomes completely weathered.		2															
	Slightly weathered light grey with some orange mottle, fractured, fine fabric SANDSTONE. Moderately strong.		2															
	2.70-2.90m - Moderately fractured same materials as above, rootlets present.		22	3				MS	SW	VC		2.40m - J, 40°	RC	100	30			
	2.90-3.20m - Recovered as: silty SAND, brownish orange. Loosely packed, dry to moist, low plasticity.		23															
	Moderately weathered dark grey with light brown and orange mottle, fractured, interbedded SANDSTONE and SILTSTONE. Sst = strong, siltst = weak.		4					W	MW	VC			RC	100	10			
	3.60-4.05m - Becomes moderately thickly bedded and more mudstone dominant.		4															
4.05-4.20m - Recovered as: medium to fine gravel with some silt and sand, greenish grey. Loosely packed, moist. Silt, low plasticity.		4																
Slightly weathered dark grey with orange mottle, fractured, indistinctly bedded SILTSTONE. Moderately strong.		20	5				MS	SW	C									
4.30-4.70m - Discontinuities: extremely closely spaced very narrow to closely spaced closed aperture.		20																
4.90-5.20m - Discontinuities: becomes thinly bedded, thinly laminated, sub-horizonal planar bedding.		20																
5.20-5.40m - Orange staining increasing.		20					W	MW			5.30m - J, 60° 5.31m - J, 40°	RC	80	0				
5.40-5.55m - Minor orange mottle.		20																
Core loss.		20																
END OF BOREHOLE AT 6m - Target Depth Reached		6																
		18	7															
		8																
		16	9															

BOREHOLE SOIL/ROCK LOG A4 - WSP_Mt COOEEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 1/11/2022
 Drilling Co.: McMillan Drilling
 Logged by: N. Ahern

Finished: 1/11/2022
 Drilling Rig: Hanjin D&B-8D - track
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: Eastern most corner of site, 20m south of railway
 Mt Cooee Landfill, Balclutha

Coordinates: 1350492 E 4873800 N
Ref. Grid: NZTM **Depth:** 6 m
R.L.: Approx. 25 m **Inclination:** Vertical
Datum: NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH7.1
BH7 Box 1: 0.0m to 3.0m



Photo BH7.2
BH7 Box 2: 3.0m to 6.0m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 1/11/2022
Drilling Co.: McMillan Drilling
Logged by: N. Ahern

Finished: 1/11/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH8

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Eastern area of site, 80m north of BH06
 Mt Cooee Landfill, Balclutha

Coordinates: 1350323 E 4873768 N
 Ref. Grid: NZTM
 R.L.: Approx. 16 m
 Datum: NZ Vertical Datum 2016
 Depth: 4.3 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS	
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE	ROCK STRENGTH						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING		BASE OF HOLE & WATER LEVEL
Caples Terrane	Moderately weathered dark grey to greenish grey with white specks, highly fractured SANDSTONE. Weak. Recovered as: coarse to fine gravel, with some sand. Gravel; subangular. Sand; coarse. 0.20-0.40m - Becomes completely weathered.		0					W	MW	EC		Lab: 0.0 - 2.8m UCS testing.						Grout	
	Slightly weathered greenish grey with white specks, coarse grained, veined, indistinctly bedded SANDSTONE. Weak to moderately strong.		1									0.40m - Vein, N	RC	100	0				
	1.25-1.50m - Crushed zone. Recovered as: coarse to fine GRAVEL with minor sand. Gravel; angular. Sand; coarse. 1.50m - Becomes light greenish grey and coarse-grained.		2					VW	MS	SW	W	EC	1.25m - CZ						
	2.50-4.30m - Crushed zone. Recovered as: COBBLES with some gravel and minor silt and sand. Cobbles and gravel; subangular, strong. Sand; fine to medium. 2.70-2.85m - Becomes moderately weathered. Very weak. Recovered as: COBBLES with some gravel and sand. Cobbles and gravel; subangular. Core loss. Moderately weathered greenish grey with minor white specks, coarse grained highly fractured, indistinctly bedded SANDSTONE. Very weak. Recovered as: COBBLES with some gravel and sand. Cobbles and gravel; subangular.		3					VW	HW	VC			1.50m - Vein, 80°, MW						
			4									2.00m - Vein, 75°, N	RC	95	60				
			4									2.50m - CZ							
			4									3.05m - Vein, VN 3.10-4.10m - Highly fractured insitu rock. Disturbed on removal from core catcher.	RC	90	53				
	END OF BOREHOLE AT 4.3m - Target Depth Reached		4.3															SWL 0.60m	
			5																
			6																
			7																
			8																
			9																
			10																
			11																
			12																

BOREHOLE SOIL/ROCK LOG A4 - WSP_Mt COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 Geotechnical borehole
 Elevation is estimated from Google Earth
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 3/11/2022
 Drilling Co.: McMillan Drilling
 Logged by: N. Ahern

Finished: 3/11/2022
 Drilling Rig: Hanjin D&B-8D - track
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: Eastern area of site, 80m north of BH06
 Mt Cooee Landfill, Balclutha

Coordinates: 1350323 E 4873768 N
Ref. Grid: NZTM
R.L.: Approx. 16 m
Datum: NZ Vertical Datum 2016
Depth: 4.3 m
Inclination: Vertical

PHOTOGRAPHS



Photo BH8.1
BH8 Box 1: 0.0m to 2.1m



Photo BH8.2
BH8 Box 2: 2.1m to 4.3m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 Geotechnical borehole
 Elevation is estimated from Google Earth
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 3/11/2022
Drilling Co.: McMillan Drilling
Logged by: N. Ahern

Finished: 3/11/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH9

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Eastern area of site, middle of excavation
 Mt Cooee Landfill, Balclutha

Coordinates: 1350377 E 4873747 N
 Ref. Grid: NZTM
 R.L.: Approx. 20 m
 Datum: NZ Vertical Datum 2016
 Depth: 6.9 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS
					SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE	ROCK STRENGTH						ROCK WEATHERING	ROCK DEFECT SPACING	SAMPLE TYPE	TCR (%)	ROD (%)	
Caples Terrane	Highly weathered to completely weathered light grey with some orange mottles, slightly interbedded SANDSTONE and SILTSTONE. Weak to moderately strong; bedding is thinly laminated and gently inclined, smooth undulating. Recovered as: cobbly GRAVEL with minor trace sand and silt. Cobbles; subangular to subrounded (possibly due to drilling). Gravel; fine to coarse, angular. Core loss. HW to CW interbedded SANDSTONE and SILTSTONE. As above. Core loss.		1		60+	42// 60 for 25mm	W	HW	EC				RC	60	0	Rotary cored PQ size wireline (85 mm nom. dia. core)	Grout	
			2				W	HW	EC				SPT	100				
			3				W	HW	EC				RC	47	0			
		HW to CW interbedded SANDSTONE and SILTSTONE. As above. Core loss.		4									RC	30	0			
				5		60+	5// 1/46 for 25mm	EW MS	CW SW	EC C				SPT	100			
	4.50-4.70m - Completely weathered. Recovered as: silty SAND with minor gravel and cobbles, dark grey. Moist. Sand; coarse to medium. Gravel; fine to coarse, subangular. Silt; non-plastic. Slightly weathered, light bluish grey with minor white specks, indistinctly interbedded, fine fabric SANDSTONE and SILTSTONE. Strong. 5.90m - Becomes light grey and moderately strong. Core loss.		6				S MS	EC C VC C C EC		35 40			RC	100	50	SWL 1.70m		
	5.10-5.25m - Broken to gravel by drilling. 5.40-5.50m - Broken to gravel by drilling. 5.90m - J, 35°, SL, clean 6.00m - J, 40°, SL, clean 6.20-6.60m - Broken to gravel by drilling.		7										RC	100	0	SWL 0.00m		
	END OF BOREHOLE AT 6.9m - Target Depth Reached		7															
			8															
			9															
			10															

BOREHOLE SOIL/ROCK LOG A4 - WSP_Mt COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Elevation is estimated from Google Earth
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 2/11/2022
 Drilling Co.: McMillan Drilling
 Logged by: N. Ahern

Finished: 3/11/2022
 Drilling Rig: Hanjin D&B-8D - track
 Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: Eastern area of site, middle of excavation
 Mt Cooee Landfill, Balclutha

Coordinates: 1350377 E 4873747 N
Ref. Grid: NZTM
R.L.: Approx. 20 m
Datum: NZ Vertical Datum 2016
Depth: 6.9 m
Inclination: Vertical

PHOTOGRAPHS



Photo BH9.1
BH9 Box 1: 0.0m to 5.5m



Photo BH9.2
BH9 Box 2: 5.5m to 6.9m

BOREHOLE SOIL/ROCK LOG A4 - WSP MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Elevation is estimated from Google Earth
 Core loss placed at end of run by default
 123mm OD Rotary Coring

Started: 2/11/2022
Drilling Co.: McMillan Drilling
Logged by: N. Ahern

Finished: 3/11/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Borehole No. BH10

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Eastern edge of site, 20m from boundary
 Mt Cooee Landfill, Balclutha

Coordinates: 1350458 E 4873714 N
 Ref. Grid: NZTM
 R.L.: Approx. 26 m
 Datum: NZ Vertical Datum 2016
 Depth: 10 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m)	DEPTH (m)	GRAPHIC LOG	TESTS			ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE			DRILLING		INSTALLATION DETAILS	
					SPT N° VALUE	SPT BLOW COUNTS OR SHEAR VALUE	ROCK STRENGTH						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	CASING		BASE OF HOLE & WATER LEVEL
TS	TOPSOIL with grass and rootlets.																		
Fill	Clayey SILT with trace gravel, light brown with black specks, homogenous. Firm to stiff, moist, low plasticity. 0.65m - Becomes brownish orange and firm.													RC	100	0			
Caples Terrane	Completely weathered brownish orange highly fractured, fine fabric SANDSTONE. Extremely weak. Recovered as: SILT with some clay and trace gravel, homogenous. Firm, moist, low plasticity. Minor rootlets present. Gravel corestones are very weak. 1.42-2.75m - Remoulds to: clayey SAND with minor silt and gravel, orangish brown, homogenous. Moist, low plasticity. Gravel: fine to coarse, HW - CW Sandstone, very weak. Sand: medium to coarse, angular to subangular. Fines: Soft.	1			22	6// 5/5/6/6								SPT	100	0			
	2.45-2.75m - Trace rootlets.	2			57	13// 10/15/14/18	EW	CW	EC					SPT	100	0			
	Grading to highly weathered, dark brown with orange weathering and white specks, fractured, fine fabric SANDSTONE. Extremely weak. Recovered as: sandy GRAVEL with minor silt. Moist, non-plastic. Gravel: fine to coarse, angular to subangular. Sand: fine to coarse.	3				60+	21// 17/20/23 for 70mm	HW						SPT	100	0			
	Highly weathered, dark orangish brown highly fractured SANDSTONE. Very weak to weak. Recovered as: Sandy GRAVEL with some cobbles and minor silt. Low plasticity. Gravel: fine to medium, angular to subangular. Sand: fine to coarse, angular to subangular.	4				57	18// 12/12/16/17	VW						SPT	100	0			
	Moderately weathered, orangish brown fractured SANDSTONE. Weak. Recovered as: gravelly COBBLES with some sand. Cobbles max 100mm, subangular. Sand: medium to coarse, rounded.	5				60+	27// 51/9 for 5mm	W	MW	VC				RC	100	0			
	Slightly weathered, orangish brown with oxidised defects, fractured SANDSTONE. Moderately strong. Discontinuities: very closely spaced closed joints, cross-cutting and sub-vertical, rough to smooth planar.	6						MS	SW	VC			5.30m - J, 70° 5.40m - J, 60°	SPT	100	0			
	5.60-5.70m - Highly fractured zone. Weak.	7						W	HW	EC				RC	100	0			
	6.10-6.15m - Crushed zone. Recovered as: sandy medium GRAVEL with minor silt. Subrounded.	8						MS	SW	VC			6.00m - J, 60° 6.10m - CZ 6.11m - J, 70° 6.15m - J, 70°	RC	100	0			
	7.20-7.90m - Highly fractured zone.	9						W	MW	VC			6.60-6.70m - Core broken during removal from catcher. 6.85m - J, 50° 6.85m - J, 70° 6.95m - J, 50° 7.20m - J, MN, silica coated 7.30m - J, 40° 7.60m - J, 30° 7.75m - J, 30° 7.90-8.80m - Disturbed on removal from core catcher.	RC	100	8			
	7.90-8.50m - Recovered as: COBBLES with some gravel and sand. Cobbles and gravel; angular to subangular, weak to very weak. 8.20-8.30m - Well-rounded coarse sized gravel.	10						W	MW	VC				RC	75	0			
	8.60-8.80m - Crushed zone. Recovered as: GRAVEL with some sand and minor silt. Gravel; fine to medium, subangular. Core loss.	11						EW	CW	EC			8.60m - CZ	RC	75	0			
	Slightly weathered, light and dark grey fractured and indistinctly bedded SILTSTONE. Moderately strong.	12						MS	MW	VC			9.00m - B, PL, silica coated	RC	95	0			
9.50-9.60m - Crushed zone. Recovered as: GRAVEL with some sand. Gravel and sand; fine to coarse, subangular. 9.60-9.85m - Dark grey. Green and white vein	13						S	SW	C			9.50m - CZ 9.51m - J, 45° 9.70m - B, ST, limonite stained	RC	95	0				

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019 - VER11X.GDT - 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring
 SWL 'nilm' indicates dry well measurement

Logged in accordance with NZ Geotechnical Society Guidelines (2005). See attached key sheet for explanation of symbols.

Scale 1:50 @ A4

Started: 28/10/2022

Drilling Co.: McMillan Drilling

Logged by: C. Hall

Finished: 31/10/2022

Drilling Rig: Hanjin D&B-8D - track

Checked by: C. Parkes



Borehole No. BH10

Project: Mt Cooee Landfill - Development Plan
 Client: Clutha District Council (CDC)
 Project No.: 6-CO082.00
 Location: Eastern edge of site, 20m from boundary
 Mt Cooee Landfill, Balclutha

Coordinates: 1350458 E 4873714 N
 Ref. Grid: NZTM
 R.L.: Approx. 26 m
 Datum: NZ Vertical Datum 2016
 Depth: 10 m
 Inclination: Vertical

GEOLOGY	MAIN DESCRIPTION / DETAIL DESCRIPTION	R.L. (m) DEPTH (m)	GRAPHIC LOG	TESTS		ROCK STRENGTH	ROCK WEATHERING	ROCK DEFECT SPACING	DEFECT DIP degrees	DEFECTS / NOTES / OTHER TESTS	CORE		DRILLING		INSTALLATION DETAILS
				SPT 'N' VALUE	SPT BLOW COUNTS OR SHEAR VALUE						SAMPLE TYPE	TCR (%)	RQD (%)	DRILLING METHOD	
	precipitation. Defects are subvertical. Core loss. END OF BOREHOLE AT 10m - Target Depth Reached	6 11 12 13 14 15 16 17 18 19													

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring
 SWL 'nilm' indicates dry well measurement

Started: 28/10/2022

Finished: 31/10/2022

Drilling Co.: McMillan Drilling

Drilling Rig: Hanjin D&B-8D - track

Logged by: C. Hall

Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: Eastern edge of site, 20m from boundary
 Mt Cooee Landfill, Balclutha

Coordinates: 1350458 E 4873714 N
Ref. Grid: NZTM
R.L.: Approx. 26 m
Datum: NZ Vertical Datum 2016
Depth: 10 m
Inclination: Vertical

PHOTOGRAPHS



Photo BH10.1
BH10 Box 1: 0.0m to 2.5m



Photo BH10.2
BH10 Box 2: 2.5m to 5.0m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring
 SWL 'nilm' indicates dry well measurement

Started: 28/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 31/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes

Project: Mt Cooee Landfill - Development Plan
Client: Clutha District Council (CDC)
Project No.: 6-CO082.00
Location: Eastern edge of site, 20m from boundary
 Mt Cooee Landfill, Balclutha

Coordinates: 1350458 E 4873714 N
Ref. Grid: NZTM **Depth:** 10 m
R.L.: Approx. 26 m **Inclination:** Vertical
Datum: NZ Vertical Datum 2016

PHOTOGRAPHS



Photo BH10.3
BH10 Box 3: 5.0m to 7.2m




Photo BH10.4
BH10 Box 4: 7.2m to 10.0m

BOREHOLE SOIL/ROCK LOG A4 - WSP - MT COOEE BOREHOLE LOGS - V0.3.GPJ WSP-OPUS2019_VER11X.GDT 30/3/23

Notes:
 SPT hammer energy ratio 91%
 Geotechnical borehole
 Core loss placed at end of run by default
 123mm OD Rotary Coring
 SWL 'nilm' indicates dry well measurement

Started: 28/10/2022
Drilling Co.: McMillan Drilling
Logged by: C. Hall

Finished: 31/10/2022
Drilling Rig: Hanjin D&B-8D - track
Checked by: C. Parkes



Appendix D
Geological Mapping
Photographs and
Geological Sections



2021 Site 1 observations

2021/2023 Site 2 observations

2023 Existing Cut slope Sections 1 to 3

2021/2023 Site 3 Landfill Expansion Area

Key:

Break in slope angle:

Approximate orientations of photographs:

Measured orientation of geological features:

Geological site mapping areas:

Inferred shear zones - approximate dip direction related to text direction

0 75 150 m

Photo 1 (below): Steeply dipping beds to the southwest

Photo 2 (right): 5 - 10 m thick SW - MW oxidised zone overlying interbedded sandstone and siltstone





Photo 1

Photo 2

Photo 3

Photo 4

Photo 4 (above): Cataclasite shear zone observed, approximate dip angle is 45 to the west

Photo 3 (left): Inferred contact between alluvium and SW - MW sandstone and siltstone



WSP
197 Rattray Street
Dunedin CBD
Dunedin 9016

Project
Mt Cooe Landfill Expansion

Description
Geological observation photographs - 2021 Site 1

Drawn by
CH

Checked by
NT





Photo 1



Photo 2




Photo 3

sub-horizontal interbedded sandstone and siltstone beds

Localised shear zones with slickensides



Photo 4

Quartz veins cross-cut by jointing




Photo 5

Cataclasite, approximate dip angle 45 degrees to the south



2021/2023 Site 2 observations



WSP
197 Rattray Street
Dunedin CBD
Dunedin 9016

Project Mt Cooee Landfill Expansion	
Description Geological observation photographs - 2021/2023 Site 2	
Drawn by CH	Checked by NT




Section 3



Section 2



Section 1



CW to HW



Slightly dipping bedding

HW to MW



Subhorizontal bedding

HW to MW



SW to Fresh



2023 Existing Cut slope Sections 1 to 3



WSP
197 Rattray Street
Dunedin CBD
Dunedin 9016

Project Mt Cooee Landfill Expansion	
Description Geological observation photographs - 2023 Existing cut slope sections	
Drawn by CH	Checked by NT




Photo 1




Photo 2




Photo 5



Photo 3





Photo 4





2021/2023 Site 3 Landfill Expansion Area



WSP
197 Rattray Street
Dunedin CBD
Dunedin 9016

Project Mt Cooee Landfill Expansion Site photographs	
Description Geological observation - 2021/2023 Landfill expansion area	
Drawn by CH	Checked by NT

Western Geological Section A - A'



Legend

Geology model with proposed landfill

- Current Landfill
- Topsoil
- Alluvium
- HW to MW sandstone and siltstone
- SW to Fresh sandstone and siltstone
- - - Inferred Groundwater Table



Notes:

Distance to borehole from section is given in metres below borehole ID.
 Profile and geological contacts extrapolated based on borehole information. Actual conditions on-site may vary to those represented in these sections.

Location

Scale: 1:680
 Vertical exaggeration: 1x
 A: 359488, 757432
 A': 359682, 757555

Eastern Geological Section B-B'



Legend

Geology model with proposed landfill

- Current Landfill
- Proposed Landfill
- Topsoil
- Alluvium
- HW to MW sandstone and siltstone
- SW to Fresh sandstone and siltstone
- - - Inferred Groundwater Table

Notes:

Distance to borehole from section is given in metres below borehole ID.
 Profile and geological contacts extrapolated based on borehole information. Actual conditions on-site may vary to those represented in these sections.

Location

Scale: 1:880
 Vertical exaggeration: 1x

B: 359752, 757152
 B': 359896, 757447



Appendix E Selected Liquefaction Assessment Outputs

SPT BASED LIQUEFACTION ANALYSIS REPORT




Project title : Mount Cooee Landfill Development

Location : Balclutha, Otago

Borehole Name : BH1

:: Input parameters and analysis properties ::

Analysis method:	Idriss & Boulanger 2014	G.W.T. (in-situ):	2.00	EQ site conditions:	Same as initial
Fines correction method:	Idriss & Boulanger 2014	G.W.T. (earthq.):	2.00		
Sampling method:	Standard Sample	Earthquake magnitude M_w :	6.00		
Borehole diameter:	65 mm to 115 mm	Peak ground acceleration:	0.26		
Rod length:	1.50	SPT results rounding mode:	Nearest		
Hammer energy ratio:	1.51				



:: Cyclic Stress Ratio fully adjusted (CSR*) numeric results ::

No	Depth (m)	Weight (kN/m ³)	u ₀ (kPa)	σ _v (kPa)	Ext. Load (kPa)	σ' _v (kPa)	r _d	CSR	K _σ	MSF _{max}	MSF	CSR*
1	1.50	17.00	0.00	25.50	0.00	25.50	0.99	0.167	1.10	1.42	1.48	2.000
2	3.00	17.00	9.81	51.00	0.00	41.19	0.96	0.201	1.10	1.32	1.48	0.153
3	4.50	17.00	24.53	76.50	0.00	51.97	0.93	0.231	1.09	1.45	1.48	0.167
4	6.00	17.00	39.24	102.00	0.00	62.76	0.90	0.246	1.06	1.38	1.48	0.189
5	7.50	17.00	53.96	127.50	0.00	73.54	0.86	0.252	1.03	1.14	1.48	2.000
6	9.00	17.00	68.67	153.00	0.00	84.33	0.82	0.253	1.05	2.20	1.48	2.000

Layer set as 'non-liquefiable due to have PI value of 14 from testing and BH description'

Rock, hence set as non-liquefiable

Abbreviations

Depth: Depth from free surface where SPT was performed (m) during eq.
 u₀: Water pressure at test point (kPa) during eq.
 σ_v: Total overburden pressure at test point (kPa) during eq.
 σ'_v: Effective overburden pressure based on GWT during earthquake (kPa) during eq.
 r_d: Nonlinear shear mass factor
 CSR: Cyclic Stress Ratio
 MSF: Effective overburden stress factor
 K_σ: Magnitude Scaling Factor
 CSR*: CSR fully adjusted

:: Cyclic Resistance Ratio (CRR) numeric results ::

No	Depth (m)	Fines %	u ₀ (kPa)	σ _v (kPa)	σ' _v (kPa)	N _{SPT}	C _N	C _R	C _B	C _S	C _E	N ₁₍₆₀₎	Δ(N ₁) ₆₀	N _{1(60),CS}	CRR _{7.5}	F.S.
1	1.50	50.00	0.00	25.50	25.50	6	1.70	0.80	1.00	1.00	1.51	12	5.61	18	4.000	2.00
2	3.00	50.00	9.81	51.00	41.19	5	1.55	0.85	1.00	1.00	1.51	9	5.61	15	0.156	1.02
3	4.50	50.00	24.53	76.50	51.97	7	1.35	0.95	1.00	1.00	1.51	13	5.61	19	0.194	1.16
4	6.00	50.00	39.24	102.00	62.76	6	1.25	0.95	1.00	1.00	1.51	11	5.61	17	0.174	0.92
5	7.50	90.00	53.96	127.50	73.54	1	1.20	0.95	1.00	1.00	1.51	1	5.51	7	4.000	2.00
6	9.00	50.00	68.67	153.00	84.33	50	1.05	1.00	1.00	1.00	1.51	79	5.61	50	4.000	2.00

Abbreviations

Depth: Depth from free surface where SPT was performed (m)
 Weight: Soil unit weight from previous test point to current (kN/m³)
 u₀: Water pressure at test point (kPa)
 σ_v: Total overburden pressure at test point (kPa)
 σ'_v: Effective overburden pressure based on in situ GWT (kPa)
 N_{SPT}: Number of blows count in the field (blows/30 cm)
 C_N: Overburden pressure factor
 C_E: Energy ratio factor
 C_B: Borehole diameter factor
 C_R: Rod length factor
 C_S: Sampling method factor
 N₁₍₆₀₎: Number of blows corrected for 60% energy
 ΔN_{1(60),CS}: Fines correction
 N_{1(60),CS}: Number of blows corrected for 60% energy and fines
 CRR_{7.5}: Cyclic Resistance Ratio for M_w 7.50
 F.S.: Factor of safety against liquefaction

SPT BASED LIQUEFACTION ANALYSIS REPORT


Project title : Mt Cooee Landfill Development

Location : Balclutha, Otago

Borehole Name : BH1

:: Input parameters and analysis properties ::

Analysis method:	Idriss & Boulanger 2014	G.W.T. (in-situ):	0.00	EQ site conditions:	Same as initial
Fines correction method:	Idriss & Boulanger 2014	G.W.T. (earthq.):	2.00		
Sampling method:	Standard Sample	Earthquake magnitude M_w :	6.00		
Borehole diameter:	65 mm to 115 mm	Peak ground acceleration:	0.26		
Rod length:	1.50	SPT results rounding mode:	Nearest		
Hammer energy ratio:	1.51				



:: Cyclic Stress Ratio fully adjusted (CSR*) numeric results ::

No	Depth (m)	Weight (kN/m ³)	u ₀ (kPa)	σ _v (kPa)	Ext. Load (kPa)	σ' _v (kPa)	r _d	CSR	K _σ	MSF _{max}	MSF	CSR*
1	1.50	17.00	0.00	25.50	0.00	25.50	0.99	0.167	1.10	1.38	1.48	2.000
2	3.00	17.00	9.81	51.00	0.00	41.19	0.96	0.201	1.10	1.32	1.48	0.153
3	4.50	17.00	24.53	76.50	0.00	51.97	0.93	0.231	1.09	1.53	1.48	0.160
4	6.00	17.00	39.24	102.00	0.00	62.76	0.90	0.246	1.06	1.42	1.48	0.186
5	7.50	17.00	53.96	127.50	0.00	73.54	0.86	0.252	1.03	1.14	1.48	2.000
6	9.00	17.00	68.67	153.00	0.00	84.33	0.82	0.253	1.05	2.20	1.48	2.000

Abbreviations

- Depth: Depth from free surface where SPT was performed (m) during eq.
- u₀: Water pressure at test point (kPa) during eq.
- σ_v: Total overburden pressure at test point (kPa) during eq.
- σ'_v: Effective overburden pressure based on GWT during earthquake (kPa) during eq.
- r_d: Nonlinear shear mass factor
- CSR: Cyclic Stress Ratio
- MSF: Effective overburden stress factor
- K_σ: Magnitude Scaling Factor
- CSR*: CSR fully adjusted

Reduced fines contents, quite conservative

:: Cyclic Resistance Ratio (CRR) numeric results ::

No	Depth (m)	Fines %	u ₀ (kPa)	σ _v (kPa)	σ' _v (kPa)	N _{SPT}	C _N	C _R	C _B	C _S	C _E	N ₁₍₆₀₎	Δ(N ₁) ₆₀	N _{1(60),CS}	CRR _{7.5}	F.S.
1	1.50	30.00	14.72	25.50	10.78	6	1.70	0.80	1.00	1.00	1.51	12	5.36	17	4.000	2.00
2	3.00	30.00	29.43	51.00	21.57	5	1.70	0.85	1.00	1.00	1.51	10	5.36	15	0.156	1.02
3	4.50	30.00	44.15	76.50	32.35	7	1.64	0.95	1.00	1.00	1.51	16	5.36	21	0.219	1.37
4	6.00	30.00	58.86	102.00	43.14	6	1.48	0.95	1.00	1.00	1.51	13	5.36	18	0.184	0.99
5	7.50	70.00	73.58	127.50	53.92	1	1.44	0.95	1.00	1.00	1.51	1	5.57	7	4.000	2.00
6	9.00	30.00	88.29	153.00	64.71	50	1.13	1.00	1.00	1.00	1.51	84	5.36	50	4.000	2.00

Abbreviations

- Depth: Depth from free surface where SPT was performed (m)
- Weight: Soil unit weight from previous test point to current (kN/m³)
- u₀: Water pressure at test point (kPa)
- σ_v: Total overburden pressure at test point (kPa)
- σ'_v: Effective overburden pressure based on in situ GWT (kPa)
- N_{SPT}: Number of blows count in the field (blows/30 cm)
- C_N: Overburden pressure factor
- C_E: Energy ratio factor
- C_B: Borehole diameter factor
- C_R: Rod length factor
- C_S: Sampling method factor
- N₁₍₆₀₎: Number of blows corrected for 60% energy
- ΔN_{1(60),CS}: Fines correction
- N_{1(60),CS}: Number of blows corrected for 60% energy and fines
- CRR_{7.5}: Cyclic Resistance Ratio for M_w 7.50
- F.S.: Factor of safety against liquefaction



Appendix F


Selected Slope/W

Outputs

Horz Seismic Coef.:
Method: Morgenstern-Price

Proposed Landfill - Section 1 Outputs

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.1 Static - Long term

6-CO082.00

Date: 04/04/2023


Scale: 1:700

By: NT

Horz Seismic Coef.:

Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.2 Static - Short Term (High GWL)

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.04
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

1.3 Seismic - SLS

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.4 Seismic - DCLS

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.:
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Dark Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

2.1 Static - Long term

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.:
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Dark Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

2.2 Static - Short Term (High GWL)

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.04
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

2.3 Seismic - SLS

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Dark Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

2.4 Seismic - DCLS

6-CO082.00


Date: 04/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Total Cohesion (kPa)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Green	Unit 2 - Alluvial Deposits (Undrained)	Undrained (Phi=0)	17	30				1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21		20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23		30	44	0	1



Mt Cooe Landfill Development Plan

2.5 Seismic - DCLS (Undrained sensitivity)

6-CO082.00

Date: 04/04/2023


Scale: 1:700

By: NT

Horz Seismic Coef.:
Method: Morgenstern-Price

Proposed Landfill - Section 2 Outputs

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Light Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

1.1 Static - Long term

6-CO082.00


Date: 06/04/2023

Scale: 1:700


By: NT

Horz Seismic Coef.:
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1




N 02
 SECTION BETWEEN CH: 0.00 AND 226.20


	Mt Cooe Landfill Development Plan	1.2 Static - Short Term (High GWL)	6-CO082.00	Date: 06/04/2023
			Scale: 1:700	By: NT

Horz Seismic Coef.: 0.04
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Light Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1




N 02
 SECTION BETWEEN CH: 0.00 AND 226.20

	Mt Cooe Landfill Development Plan	1.3 Seismic - SLS	6-CO082.00	Date: 06/04/2023
			Scale: 1:700	By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Light Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1





Mt Cooee Landfill Development Plan
 1.4 Seismic - DCLS

6-CO082.00 Date: 06/04/2023
 Scale: 1:700 By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price


Color	Name	Slope Stability Material Model	Unit Weight (kN/m³)	Total Cohesion (kPa)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16		1	25	0	1
Green	Unit 2 - Alluvial Deposits (Undrained)	Undrained (Phi=0)	17	30				1
Orange	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Undrained)	Undrained (Phi=0)	21	400				1
Purple	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Undrained)	Undrained (Phi=0)	23	750				1



	Mt Cooe Landfill Development Plan	1.5 Seismic - DCLS (Undrained sensitivity)	6-CO082.00	Date: 06/04/2023
			Scale: 1:700	By: NT

Horz Seismic Coef.:
Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Light Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



N 02
N BETWEEN CH: 0.00 AND 226.20



Mt Cooe Landfill Development Plan

2.1 Static - Long term

6-CO082.00


Date: 06/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.:
Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Light Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



N 02
N BETWEEN CH: 0.00 AND 226.20



Mt Cooe Landfill Development Plan

2.2 Static - Short Term (High GWL)

6-CO082.00


Date: 06/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.04
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



N 02
 N BETWEEN CH: 0.00 AND 226.20



Mt Cooe Landfill Development Plan

2.3 Seismic - SLS

6-CO082.00


Date: 06/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Light Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16	1	25	0	1
Light Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	28	0	1
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



N 02
 N BETWEEN CH: 0.00 AND 226.20



Mt Cooe Landfill Development Plan

2.4 Seismic - DCLS

6-CO082.00


Date: 06/04/2023

Scale: 1:700

By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m³)	Total Cohesion (kPa)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Green	Existing Landfill (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Light Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Yellow	Unit 1 - Topsoil	Mohr-Coulomb	16		1	25	0	1
Green	Unit 2 - Alluvial Deposits (Undrained)	Undrained (Phi=0)	17	30				1
Orange	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Undrained)	Undrained (Phi=0)	21	400				1
Purple	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Undrained)	Undrained (Phi=0)	23	750				1



N 02
 SECTION BETWEEN CH: 0.00 AND 226.20



Mt Cooe Landfill Development Plan

2.5 Seismic - DCLS (Undrained sensitivity)

6-CO082.00

Date: 06/04/2023


Scale: 1:700

By: NT

Horz Seismic Coef.:
Method: Morgenstern-Price

Existing Landfill Stability Outputs

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Green	Existing Clay Bund (Drained)	Mohr-Coulomb	18	3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	24	0	1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.1 Static - Long term

6-CO082.00


Date: 06/04/2023

Scale: 1:400

By: NT

Horz Seismic Coef.:
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Green	Existing Clay Bund (Drained)	Mohr-Coulomb	18	3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	24	0	1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

1.2 Static - Short Term (High GWL)

6-CO082.00

Date: 06/04/2023


Scale: 1:400

By: NT

Horz Seismic Coef.:

Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Green	Existing Clay Bund (Drained)	Mohr-Coulomb	18	3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	24	0	1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.2 Static - Short Term (High GWL)sensitivity

6-CO082.00


Date: 06/04/2023

Scale: 1:400

By: NT

Horz Seismic Coef.: 0.06
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Green	Existing Clay Bund (Drained)	Mohr-Coulomb	18	3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	24	0	1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

1.3 Seismic - SLS

6-CO082.00

Date: 06/04/2023


Scale: 1:400

By: NT

Horz Seismic Coef.: 0.06

Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Total Cohesion (kPa)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Yellow	Existing Clay Bund (Drained)	Mohr-Coulomb	18		3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Green	Unit 2 - Alluvial Deposits (Undrained)	Undrained (Phi=0)	17	30				1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21		20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23		30	44	0	1



Mt Cooee Landfill Development Plan

1.3 Seismic - SLS (Undrained)

6-CO082.00


Date: 06/04/2023

Scale: 1:400

By: NT

Horz Seismic Coef.: 0.23
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Green	Existing Clay Bund (Drained)	Mohr-Coulomb	18	3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13	5	25	0	1
Orange	Unit 2 - Alluvial Deposits (Drained)	Mohr-Coulomb	17	1	24	0	1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.4 Seismic - DCLS

6-CO082.00


Date: 06/04/2023

Scale: 1:400

By: NT

Horz Seismic Coef.: 0.23
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Total Cohesion (kPa)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Yellow	Existing Clay Bund (Drained)	Mohr-Coulomb	18		3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Green	Unit 2 - Alluvial Deposits (Undrained)	Undrained (Phi=0)	17	30				1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21		20	40	0	1
Cyan	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Undrained)	Undrained (Phi=0)	23	750				1



Mt Cooe Landfill Development Plan

1.5 Seismic - DCLS (Undrained sensitivity)

6-CO082.00


Date: 06/04/2023

Scale: 1:400

By: NT

Horz Seismic Coef.: 0.08
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Total Cohesion (kPa)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Yellow	Existing Clay Bund (Drained)	Mohr-Coulomb	18		3	28	0	1
Red	Refuse / Waste (Drained) - Nominal Parameters	Mohr-Coulomb	13		5	25	0	1
Green	Unit 2 - Alluvial Deposits (Undrained)	Undrained (Phi=0)	17	30				1
Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21		20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23		30	44	0	1



Mt Cooee Landfill Development Plan

1.6 Seismic - Yield Acceleration (Undrained)

6-CO082.00

Date: 06/04/2023


Scale: 1:400

By: NT

Horz Seismic Coef.:
 Method: Morgenstern-Price

Transfer Station Cut Stability Outputs

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.1 Static - Long term (Unit 3b)

6-CO082.00


Date: 06/04/2023

Scale: 1:300

By: NT

Horz Seismic Coef.:
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooe Landfill Development Plan

1.2 Static - Short Term (High GWL)

6-CO082.00


Date: 06/04/2023

Scale: 1:300

By: NT

Horz Seismic Coef.: 0.04
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

1.3 Seismic - SLS

6-CO082.00

Date: 06/04/2023


Scale: 1:300

By: NT

Horz Seismic Coef.: 0.17

Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Piezometric Surface
Light Purple	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	21	20	40	0	1
Blue	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0	1



Mt Cooee Landfill Development Plan

1.4 Seismic - DCLS

6-CO082.00


Date: 06/04/2023

Scale: 1:300

By: NT

Horz Seismic Coef.: 0.17
 Method: Morgenstern-Price

Color	Name	Slope Stability Material Model	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (°)	Phi-B (°)	Total Cohesion (kPa)	Piezom Surface
■	Unit 3b - Highly to moderately weathered, very weak to weak SANDSTONE/SILTSTONE (Undrained)	Undrained (Phi=0)	21				400	1
■	Unit 3c - Slightly weathered, moderately strong to strong SANDSTONE/SILTSTONE (Drained)	Mohr-Coulomb	23	30	44	0		1



Mt Cooee Landfill Development Plan

1.5 Seismic - DCLS (Undrained sensitivity)

6-CO082.00

Date: 06/04/2023

Scale: 1:300

By: NT

wsp

wsp.com/nz